

Eutech PD 450



pH / mV / Dissolved Oxygen / Temperature

Affordable optical RDO technology reduces maintenance time and costs

- Maintenance free optical probe with no electrolyte eliminates hassle of replacing delicate membranes and salt build up from refilling solutions
- **Switch between pH, mV, % saturation and mg/L (ppm) dissolved oxygen** – With the press of a button
- Durable waterproof and dustproof design with IP67 rating
- Large, backlit graphic display provides measurement with temperature
- Calibrate up to 5 points automatically with USA or NIST buffer groups (up to 6 points with DIN). New manual option allows calibration with up to 5 custom buffer standards
- **Auto buffer recognition** – Automatically identifies the correct pH buffer for rapid calibration
- **Calibration due alarm** – Set a visible reminder when it is time to recalibrate the meter
- **Selectable °C or °F** – Choose units to best fit your application
- Ready indicator, manual or automatic measurement hold feature and optional automatic shutoff function
- **Store up to 500 data sets** – Easy USB or RS232 output with optional data cables
- **Built-in real-time clock stamps stored data and calibration data with time and date** – Meets standards for GLP (Good Laboratory Practices)



Calibration Chamber



RDO Weight/Guard



RDO Sensor Cap



RDO Probe



Specification Table

pH	Range	-2.00 to 16.00 pH
	Resolution	0.01 pH
	Accuracy	±0.01
	Calibration	Up to 6 points: USA, NIST, DIN or custom
mV	Range	±2000 mV
	Resolution	0.1 mV ±999.9 mV; 1 mV beyond
	Accuracy	±0.2 mV +2 LSD or +0.5 % of reading; whichever is greater
	Calibration	±200 mV
Dissolved Oxygen	Range	0 to 200 %; 0 to 20 ppm/mg/L
	Resolution	0.10 %; 0.1 ppm/mg/L
	Accuracy	±2 %; ±0.1 ppm or mg/L up to 8; ±0.2 ppm or mg/L above 8
	Calibration	Zero and saturation
Temperature	Range	-10.0 to 110.0 °C (14.0 to 230.0 °F)
	Resolution	0.1 °C/°F
	Accuracy	±0.5 °C; ±0.9 °F
	Calibration	Offset in 0.1 increments, ±10 °C or ±18 °F
Display	Custom LCD with backlight	
Memory	Stores up to 500 data sets	
Output	USB or RS232	
Real-Time Clock	Time and date stamp on calibration and stored data	
Temperature Compensation	Automatic or manual from -10 to 110 °C	
Pressure & Salinity Compensation	Manual	
Power	Two AA batteries (included), >100 hours (without backlight); AC adapter (optional)	



Ordering Information

Order Code	Part No.	Description
Meter		
ECPDWP45000	01X651641	PD 450 Meter Only: Meter, two AA batteries
ECPDWP45004	01X651646	PD 450 Meter & Electrodes: Meter, pH/ATC electrode, RDO electrode with sensor cap, two AA batteries
ECPDWP45004K	01X651642	PD 450 Meter Kit: Meter, pH electrode, RDO electrode with sensor cap, two AA batteries, hard carry case, USB cable, RDO stainless steel weight/guard, RDO calibration chamber, calibration solutions
Electrodes		
ECDA9350603B	93X218879	Replacement pH electrode, submersible, single-junction, ABS, 26 mm diameter, BNC, 3 m cable
RDO3M	RDO3M	RDO probe, 3 m (10 ft) cable
RDO6M	RDO6M	RDO probe, 6 m (20 ft) cable
RDO15M	RDO15M	RDO probe, 15 m (50 ft) cable
Accessories		
RDOCAP	RDOCAP	Replacement RDO sensor cap
RDOWEIGHT	RDOWEIGHT	RDO weight, screw thread to attach to probe
RDOCALCHAMBER	RDOCALCHAMBER	Calibration chamber
60X426401	60X426401	Optional 100 / 240 VAC SMPS power adapter, 9V, 6 W
MINIPHONEUSB	MINIPHONEUSB	USB cable for 450 series, mini phone plug to USB
30X427301	30X427301	RS232 cable for 450 series, mini phone plug to RS232 9-pin (F)
ECDOZEROSOLN	01X211238	Zero oxygen solution, 0 % DO, 480 mL