

Incubator

CO₂ Incubator

Features:

- * Water tank for humidity in the chamber.
- * Air jacket: equipped with UV Lamp for sterilizing;
Water jacket: equipped with HEPA filter.
- * Equipped with USB port and LCD touch screen, the incubator can save data in real time.
- * High quality CO₂ gas filter ensures the inside gas quality.
- * SMC brand gas circuit valves ensure more stable CO₂ concentration and less consumption of CO₂ gas.
- * Microcomputer controller, LCD displays temperature curve, CO₂ concentration, run-time and timing.
- * High quality infrared sensor for accurate CO₂ concentration.
- * The working chamber adopts round angle structure, easy to clean.



LCD touch screen



CO₂ gas filter



HEPA filter (for water jacket)

Technical Parameters:

Model	BJPX-C50	BJPX-C80		BJPX-C160	
Capacity	50L	80L		160L	
Heating	Air jacket	Air jacket	Water jacket	Air jacket	Water jacket
Temp. Range	RT+5-60°C				
Control Type	Microcomputer controller				
Temp. Fluctuation	≤ ±0.2°C (at 37°C)				
Temp. Uniformity	≤ ±0.3°C (at 37°C)				
Time Setting	999h or continuous				
Alarm	Audible and visual alarm; over-temperature alarm; CO ₂ concentration alarm.				
Shelves	2 pcs/adjustable				
Material	External cold-rolled steel with painting; internal stainless steel				
Door	With inner door and external door				
CO ₂ Range	Infrared sensor, range 0-20%				
CO ₂ Control Resolution	0.1%				
Humidification Type	Water tank for natural evaporation				
Sterilization Type	UV lamp				
Ambient Temp. & Humidity	18-30°C, suggest 25±2°C; relative humidity ≤80%				
Caster	Footmaster caster				
Consumption	350W	600W	875W	650W	1000W
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110±10%, 60Hz(Optional)				
Internal Size (W*D*H)mm	337*338*443	377*410*524	428*412*522	477*473*711	528*512*722
External Size(W*D*H)mm	500*527*621	600*596*921	647*593*1070	700*666*1101	747*694*1260
Packing Size (W*D*H)mm	655*685*970	735*735*1070	725*780*1225	795*835*1250	824*877*1425
Gross Weight(kg)	68	83	108	108	145