

Catalog Number: 3324

Product Description: Corning® CellSTACK® - Universal Cap, 1 solid overcap, 2 vent caps

Component Materials:

- One Piece Universal Cap - Virgin High-Density Polyethylene, meets USP, Class VI requirements for plastic Containers and closures. Heavy metal free (meets CONEG req.) color concentrate.
- Over cap - Low Density Polyethylene
- Vent - 0.2µm PTFE membrane, meets USP, Class VI requirements for plastic containers and closures.
- Foil - Polyethylene heat sealed film

Product Dimensions:

- | | | | | | |
|-------------------------|---|--------------|------------------------|---|-----------|
| Diameter of solid cap | - | 0.690 in. | Diameter of vent cap | - | 0.770 in. |
| Height of solid cap | - | 0.562 in. | Height of vent cap | - | 0.561 in. |
| Sm diameter of air foil | - | 0.250 in. | Lg diameter of airfoil | - | 0.750 in. |
| Tolerances | - | +/- 0.05 in. | Spacing of airfoil | - | 0.750 in. |

Sterilization – Product has been sterilized and dosimetrically released per the requirements of ANSI/AAMI/ISO 11137 “Sterilization of health care products- Radiation”. Products meet a minimum Sterility Assurance Level (SAL) of 10⁻⁶.

Animal Content: Product does not contain materials of animal origin.

Quality Control Testing – Representative production samples are collected and inspected in accordance with current applicable product specifications. Inspection records are reviewed and approved by qualified personnel for product release. Key inspections and inline tests are listed below:

- Visual Inspection – Pass
- Packaging Inspection – Pass

Lot Number Designation:

8 Digit Lot Number: First 3 digits – Julian date, start of manufacturing; Next 2 digits – Year of manufacture; Last 3 digits – Batch identification.