# Corning Incorporated Life Sciences

Registered ISO 9001:2008

# **Product Description**

Catalog Number:

99999-15

**Product Description:** 

PYREX® Screw Cap, Disposable, Phenolic, Rubber Liner, G.P.I. 415-15

# **Component Materials:**

Cap - Phenolic (Wood Fill) Liner - Rubber

Attributes:

Product Dimensions - 18 mm OD x 16 mm High

## Autoclaving:

Disposable screw caps can be autoclaved 1 time at the standard autoclave cycle of 121°C at 15 psi for 15 minutes. Caps should be loose on the container to avoid liners being pulled out by the vacuum created as the assembly cools.

### Heating / Cooling:

This product is primarily designed for a specific use that does not involve direct heating. In normal use, temperatures will be from -50° to +125°C. This is below the temperature at which thermal failure could be a problem.

### Vacuum / Pressure:

This product is a component part and not specifically rated for vacuum or pressure.

Sterilization: Shipped Not Sterile

### Lot Number Designation:

Each production lot is uniquely identified with an 8 digit lot number as follows: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Revision Date:

16 AUG 2013

Rev No: 1