Corning Incorporated Life Sciences

Registered ISO 9001:2008

Product Description

Catalog Number: 4561

Product Description: Corning ® 1536 well, tissue culture treated, black plate with clear flat bottom, high

web, low base, without lid, with barcode labels

Component Materials:

Plate walls - Cyclic Olefin Co-polymer, meets USP, Class VI requirements for plastic containers and

closures. Black cyclic olefin co-polymer concentrate

Plate bottom - Cyclic Olefin Co-polymer, meets *USP*, Class VI requirements for plastic containers and

closures.

Barcode Label - White polypropylene base, acrylic adhesive.

Special Feature:

Barcode label (format 128) on A1 long side & H12 longside.

Product Dimensions:

Length of Plate - 5.030 in. Width of Square Well @ - .070 in.

Top

Tolerances of - + .010 in. / -.015 in. Width of Plate - 3.365 in.

Dimensions for Length

Diameter well @ bottom - .059 in. Depth of Well - .244 in. Height without Lid - .315 in. Tolerances of - +/- .010 in.

Dimensions

Maximum well volume - 15µl Recommended working - 10µl

volume per well

Sterilization:

This lot has been irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 *Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization.*Sterility Assurance Level: SAL 10⁻³

Pyrogens:

The product has been tested and has met the criteria established in the current version of ANSI/AAMI ST 72:2002/(R)2010 Bacterial Endotoxins - Test methodologies, routine monitoring, and alternative to batch testing.

Results: ≤ 0.1 EU/mL (≤ 4EU/device)

Surface Characterization:

Surface is characterized to be hydrophilic and negatively charged. The negatively charged, carboxyl surface composition, has been optimized for cell attachment and growth.

Cell Attachment and Growth Characteristics:

The product has been tested for the attribute of cell attachment and growth utilizing an attachment-dependent mammalian cell line in a serum supplemented media.

Optical Characteristics:

The product is made of opaque black cyclic olefin co-polymer walls to minimize well to well crosstalk and background fluorescence and /or luminescence. The bottom is made of clear cyclic olefin co-polymer to permit direct microscopic viewing.

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures.

Visual Attributes: Visual examination of the product.

Packaging: Inspection for seal and barrier integrity, accurate labeling and correct

product configuration.

Cell Culture Treatment: Wettability test using water to insure the presence of a hydrophilic

surface.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian Date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 2