



BK-FD50S



BK-FD50T



BK-FD100S



BK-FD100T

Technical Parameters

BK-FD50S(Standard)	BK-FD50T(Stoppering)	BK-FD100S(Standard)	BK-FD100T(Stoppering)
0.7m ²	0.5m ²	1.04m ²	1.15m ²
-50°C→+70°C(no-loading)			
<-75°C(no-loading)			
≤5 Pa(no-loading)			
≥10kg		≥15kg	
/	70L		
/	Φ400*560mm		
410*510*590 mm	620*510*560mm	410*580*520mm	700*590*760mm
Shelf:480*360*18mm	Shelf:410*410*18mm	Shelf:480*360*18mm	Shelf:480*600*18mm
Tray: 475*355*25mm	Tray: 405*405*25mm	Tray: 475*355*25mm	Tray: 475*595*25mm
Shelf: 4+1, Tray: 4	Shelf: 3+1, Tray: 3	Shelf: 6+1, Tray: 6	Shelf: 4+1, Tray: 4
7L	5L	10L	11L
70mm			100mm
±1°C			
R404A + R23			
Air cooling			
Natural defrosting (option electric defrosting)	Electric defrosting	Electric defrosting	Electric defrosting
/	automatic	/	automatic
/	1050	/	2460
/	2058	/	4788
/	3075	/	8624
8L/S(29m ³ /h)			15L/S(54m ³ /h)
/	1000W	1500W	
1000W			1600W
/	1000W	/	1500W
5.5KW	6.5KW	6.5KW	7.5KW
AC380V, 50Hz/60Hz (three phase) BK-FD50S:AC220V, 50Hz/60Hz (single phase)			
600kg	800kg	700kg	1000kg
1000*850*1420mm	1490*850*1620mm	1170*830*1665mm	1640*1100*1630mm
1130*980*1620mm /565kg	1600*1040*2040mm /800kg	1320*990*1855mm /900kg	1800*1250*2100mm /1200kg
790*330*445mm (73kg)	830*370*600mm (88kg)	785*455*300mm (95kg)	800*500*500mm (70kg)

Optional: Import vacuum pump, Vacuum pump anti-return valve, Eutectic point tester, Oil mist filtration system, Vacuum adjustment device