

## Portable Autoclave

### Range of Application:

It's desk-top autoclave sterilizer which is designed for the hospital, clinic, lab, etc.  
It's mostly suitable for sterilizing of surgical, dental instruments, glassware, culture medium and biological dressing, food and goods, etc.



Timing control type

### Features:

- \* Easy operation, safe and reliable.
- \* The sealing ring is made of silicon rubber.
- \* Two safety valves keep double safety (for timing control type).
- \* It has self-adjustment function (for timing control type)
- \* It is well sealed and effectively prevents steam leakage.
- \* Over temperature & over pressure auto-protection.
- \* Electric or LPG heating (for Dual fuel Type).
- \* Immersion type electric heating pipe, thermal efficiency is high, stainless steel material tube is durable to use.
- \* Double groove pressure gauge, could clearly indicate, convenient observation, reliable performance.
- \* When at lower water level, or at the end of heat preservation time, have buzzer alarm, timing control type will automatically stop heating (for timing control type).



Anti-dry out type



Dual fuel type

### Technical Parameters:

Model	BKM-P18(D)	BKM-P24(D)	BKM-P18(A)	BKM-P24(A)	BKM-P18(B)	BKM-P24(B)		
Type	Timing control type		Anti-dry out type		Dual fuel Type			
Capacity	18L	24L	18L	24L	18L	24L		
Chamber Size(mm)	φ280*210	φ280*310	φ280*210	φ280*310	φ280*260	φ280*390		
Time Setting	1~99min		NO					
Temperature Setting	RT+5~126°C		126°C(default) or 121°C		126°C			
Consumption	2KW							
Power Supply	AC220V, 50/60Hz			AC110/220V±10%, 50/60Hz				
Working Pressure	Along with temperature change		0.142Mpa		0.14-0.16Mpa			
Package Size(W*D*H)mm	420*420*650	420*420*740	420*420*650	420*420*740	410*410*430	410*410*550		
Gross Weight(kg)	12	14	12	14	16	17		