



ROTOR SPECIFICATIONS

Type	Fixed Angle
Material	Titanium
Capacity	20 x 0.2 mL
Maximum Speed	100,000 rpm
Tube Dimensions Ø x L	7 x 20 mm
Angle	30°
K Factor	7.0
Net Weight	0.52 kg /1.1 lbs
Warranty	5 years

	RCF	RADIUS
Maximum	435,630 xg	39.0 mm
Average	383,131 xg	34.3 mm
Minimum	330,632 xg	29.6 mm

ROTOR AND ACCESSORIES ORDERING INFORMATION

S100-AT3 Rotor Package includes:

Description	Cat. No.
S100-AT3 Rotor	45585
0.2 mL PC Thick-Walled Tubes (qty. 1 pkg. of 100)	45233
Large O-ring for Cover (qty. 2)	45322
Small O-ring for Cover (qty. 2)	45276
Rotor Holding Fixture	45266
Lubricant	61556
Vacuum Grease	65937
Instruction Manual	45265

Accessories:

Description	Cat. No.
Rotor Stand	45357
Cover Opener	45173

LABWARE ORDERING INFORMATION

Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Qty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (xg)	Dims ØxL (mm)	REQUIRED TUBE CLOSURES, ADAPTERS, TOOLS & ACCESSORIES			
									Type	Cat. No.	Qty. /Pkg.	Description
0.2	0.2	PC Thick-Walled Tube	45233	100	20	100,000	435,630	7 x 20	–	–	–	–
0.2	0.2	PA Thick-Walled Tube	45234	100	20	80,000	278,803	7 x 20	–	–	–	–

© 2014 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

For more information, please visit
www.thermoscientific.com/rotors.

DSCFGMULTRAS100AT3 1114

Thermo
 SCIENTIFIC

Part of Thermo Fisher Scientific