## Corning Incorporated Life Sciences

Registered ISO 9001:2008

# **Product Description**

Catalog Number: 3726BC

Product Description: Corning ® 1536-well, tissue culture treated, solid black plate, flat bottom, with lid, with

barcode labels

**Component Materials:** 

Plate - Virgin Polystyrene, meets USP. Class VI requirements for plastic containers and

closures. Black concentrate

Lid - Virgin Polystyrene, meets *USP, Class VI* requirements for plastic containers and

closures.

Barcode Label - White polypropylene base, acrylic adhesive.

Special Feature:

Barcode label (format 128) on A1 short & A1 long side and H12 short & H12 long side.

**Product Dimensions:** 

Length of Plate - 5.030 in. Width of Square Well @ - .067 in.

Top

Width of Plate - 3.365 in. Width of Square Well @ - .0035 in. / .022cm sq.

**Bottom** 

Depth of Well - .195 in. Height with Lid - .500 in. Tolerances of - +/- .010 in. Plate Height - .410 in.

**Dimensions** 

Total well volume - 12.2µL Recommended working - 10µL

volume per well

#### Sterilization:

This lot has been irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 *Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization.*Sterility Assurance Level: SAL 10<sup>-3</sup>

Pyrogens:

The product has been tested and has met the criteria established in the current version of ANSI/AAMI ST 72:2002/(R)2010 Bacterial Endotoxins - Test methodologies, routine monitoring, and alternative to batch testing.

Results: ≤ 0.1 EU/mL ( ≤ 4EU/device)

### Surface Characterization:

Surface is characterized to be hydrophilic and negatively charged. The negativetly charged, carboxyl surface composition, has been optimized for cell attachment and growth.

#### Cell Attachment and Growth Characteristics:

The product has been tested for the attribute of cell attachment and growth utilizing an atttachment-dependent mammalian cell line in a serum supplemented media.

#### **Optical Characteristics:**

The product is made of opaque black polystyrene walls to minimize well to well crosstalk and background fluorescence and /or luminescence.

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures.

Visual Attributes: Visual examination of the product.

Packaging: Inspection for seal and barrier integrity, accurate labeling and correct

product configuration.

Cell Culture Treatment: Wettability test using water to insure the presence of a hydrophilic

surface.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian Date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 3