

INSTRUMENT / CONSUMMABLE REAGENT



Order Code	Description	
Waterproof pH Pocket Testers		
ECOPHTEST1	Waterproof EcoTestr pH 1 Tester without ATC, 1 point Calibration	
ECOPHTEST2	Waterproof EcopHTestr 2 Tester with ATC; 3 point Calibration	
EXPERTPH	Waterproof Expert pH pocket tester with ATC and temperature display, 3 point Calibration, ±0.1 pH accuracy	
Waterproof pH Testers		
PHTEST10	Waterproof pHTestr 10 Tester with ATC; ±0.1 pH accuracy	
PHTEST20	Waterproof pHTestr 20 Tester with ATC; ±0.01 pH accuracy	
PHTEST30	Waterproof pHTestr 30 Tester with ATC and Temperature Readout; ±0.01 pH resolution	
Waterproof BNC Testers		
PHTEST10BNC	Waterproof pHTestr 10 BNC Tester with MTC; BNC connector sensor; ±0.01 pH resolution (meter only – electrode to be ordered separately)	
Waterproof Spear Testers		
PHSPEAR	Waterproof pHSpeAr Tester with MTC; double-junction spear-tip electrode; ±0.01 pH accuracy	
Waterproof ORP / Redox Pocket Testers		
ORPTEST10	Waterproof ORPTestr 10 Large Dual Display Tester (-999 to +1000 mV)	
ORPTEST10BNC	Waterproof ORPTestr 10 Large Dual Display Tester; BNC connector sensor; (-999 to +1000 mV); (meter only – electrode to be ordered separately)	
Accessories		
PHSENSOR03DJ	Replacement Double Junction Sensor for pHTestr 10, 20, 30	
PHSENSORBNC	Replacement BNC Connector Sensor for pHTestr 10BNC and ORPTestr 10BNC	

Authorised Distributors

PHSENSOR04	Replacement Double Junction Spear-tip Electrode for pHSpear	
ORPSENSORDJ	Replacement Double Junction Sensor for ORPTestr 10	

Accessories

ECFC7252101B	General Purpose Plastic-body Single Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC72521R01B	General Purpose Plastic-body Single Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC7252201B	General Purpose Plastic-body Double Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC72522R01B	General Purpose Plastic-body Double Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC7960101B	General Purpose Plastic-body Single Junction Gel-Filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC7960201B	General Purpose Plastic-body Double Junction Gel-Filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	

Economy pH / ORP / Ion Handheld Meters

ECION602PLUSK	Ion 6+ pH/Ion/ORP Meter with single junction pH electrode ECFC7252101B, ATC probe & pH carrying kit set	
ECPH602PLUSK	pH 6+ pH/ORP Meter with single junction pH electrode ECFC7252101B, ATC probe & pH carrying kit set	
ECPH502PLUSK	pH 5+ pH Meter with single junction pH electrode ECFC7252101B, ATC probe & pH carrying kit set	

Note: Ion 6+ , pH 6+ & pH 5+ pH Carrying Kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, storage solution and 1 x deionised (rinse) water (60 ml each)

Waterproof pH / ORP / Ion Handheld Meters

ECPHWP15002K	Meter with double-junction pH electrode ECFC7252201B and ATC probe, Grip-Clip™, two AA batteries, hard carry case, pH buffers, storage solution, rinse solution. ORP electrode to be ordered separately	
ECPHWP45002K	pH 450 meter Kit with double-junction pH electrode ECFC7252201B and ATC probe, Grip-Clip™, two AA batteries, hard carry case, USB cable, pH buffers, storage solution, rinse solution. ORP electrode and Ion Selective Electrode to be ordered separately.	

Waterproof pH / ORP / Ion Handheld Meters

ECPHWP62042K	Waterproof CyberScan pH 620 pH/mV/Ion Meter with double junction pH electrode ECFC7252203B, ATC probe, DAS software, power adapter & pH carrying kit set	
--------------	--	--





ECPHWP61042K	Waterproof CyberScan pH 610 pH/mV Meter with double junction pH electrode ECFC7252203B, ATC probe, DAS software, power adapter & pH carrying kit set	
ECPHWP60042K	Waterproof CyberScan pH 600 pH/mV Meter with double junction pH electrode ECFC7252203B, ATC probe, DAS software, power adapter & pH carrying kit set	
Note: pH 620, pH 610 & pH 600 pH Carrying Kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, storage solution and 1 x deionised (rinse) water (60 ml each)		

Accessories

ECPH5TEM01P	ATC probe (for Ion 6+, pH 6+, pH 5+, pH 110 & pH 11 only); 1m cable length	
PHWPTEM01W	ATC Probe ATC Probe (for pH 310, pH 300, PC300 ,PC510, PH 150, CON 150, PH 450, CON 450, PC 450) 1m cable length	
ECPHWPTM01J	ATC Probe (for pH 620, 610, 600, PC650, PD650, PCD650 only); 1m cable length	
ECPHWPTM03J	ATC Probe (for pH 620, 610, 600, PC650, PD650, PCD650 only); 3m cable length	
ECFC7252101B	General Purpose Plastic-body Single Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC7252201B	General Purpose Plastic-body Double Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC7252203B	General Purpose Plastic-body Double Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 3m cable length	
ECECOPHKIT	Economy pH Carrying Kit Set – Plastic Carrying Case comprises: 1 x pH 4.01, pH 7.00 buffer solutions, storage solution and 1 x deionised (rinse) water (60 ml each)	
ECECODRYKIT	Economy Neutral Carrying Kit Set - Plastic Carrying Case comprises: 4 x empty sample bottles (60 ml)	
ECPHWP600KIT	CyberScan pH 600 series Carrying Kit Set - Plastic Carrying Case comprises: 1 x pH 4.01, pH 7.00 buffer solutions, storage solution and 1 x deionised (rinse) water (60 ml each)	
60X030130	100 /240VAC SMPS Power Adapter with US/UK/EUR/Japan plug ,9V,6W, CENTRE +ve (for Cyberscan 11 / 110 / 510/1100 / 2100 series)	
60X426401	100 /240VAC SMPS Power Adapter , 9V,6W (150, 450 and 2700 series)	
01X030132	Universal SMPS,100 /240VAC,9V,6W, CENTRE +ve Power Adapter with US/UK/EUR/Japan plug (for Cyberscan 600 series)	
01X447602	USB / IrDA Interface Adapter (for 600 Series Meter to PC Communication)	
AN-270	Dot Matrix Printer, Brand Antech	
ECFC72521R01B	General Purpose Plastic-body Single Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC72522R01B	General Purpose Plastic-body Double Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC7252205B	General Purpose Plastic-body Double Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 5m cable length	



ECFC7352901B	General Purpose Plastic-body "3-in-1" pH/Temp. Combination Electrode, 12x90mm, BNC connector, 1m cable length (for pH 5/6, Ion 6, pH 11/110, pH 510 & pH 1100/2100)	
ECFC7352901W	General Purpose Plastic-body Gel-Filled "3-in-1" pH/Temp. Combination Electrode, 12x90mm, BNC and 6 pin connector, 1m cable length (for pH 310, 300, PC300 & PC510)	
ECFC7352901J	General Purpose Plastic-body Gel-Filled "3-in-1" pH/Temp. Combination Electrode, 12x90mm, BNC and 8 pin connector, 1m cable length (for pH 620, 610, 600, PC650, PD650, PCD650 only)	
ECFG7350401B	General Purpose Glass-body Single Junction Refillable pH Combination Electrode, annular ceramic reference junction with protective sensor guard, 12x110mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC7960101B	General Purpose Plastic-body Single Junction Gel-Filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC7960201B	General Purpose Plastic-body Double Junction Gel-Filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	



pH / ORP / Ion Bench Meters

ECION70040S	Eutech Ion 700 Meter With Integral Electrode Holder & 100/240 VAC Adapter. pH and Ion Electrodes to be ordered separately	
ECPH70042S	pH 700 meter with single junction pH electrode ECFC7252101B, ATC Probe PH5TEMB01P, integral electrode holder and 100/240 VAC Adapter	
ECPH70042GS	pH 700 meter with glass body, open pore pH electrode EC620131, ATC Probe PH5TEMB01P, integral electrode holder and 100/240 VAC Adapter	
ECION270042GS	Eutech ION 2700 Meter With pH Electrode (ECFG7370101B), ATC Probe (PH5TEMB01P), Integral Electrode Holder, 100/240 VAC Adapter, RS232 cable, & pH Electrode Refill Solution. Ion Electrodes to be ordered separately	
ECPH270042GS	pH 2700 Meter with pH Electrode (ECFG7370101B), ATC Probe (PH5TEMB01P), Integral Electrode Holder, 100/240 VAC Adapter, RS232 cable	
ECPH27005E	pH 2700 meter with glass body, open pore pH electrode EC620131, ATC Probe PH5TEMB01P, integral electrode holder , 100/240 VAC Adapter and RS232 cable	
ECPH27005E-P	pH 2700 meter with glass body, open pore pH electrode EC620131, ATC Probe PH5TEMB01P, integral electrode holder , 100/240 VAC Adapter, RS232 cable and AN-270 Dot Matrix Printer	
ECPH51042S-I	CyberScan pH 510 pH/mV Meter with indigenous glass pH electrode AN-786-1 , BNC connector, 1m cable length, indigenous ATC probe , integral electrode holder & power adapter	
ECPH51042S	CyberScan pH 510 pH/mV Meter with single junction pH electrode ECFC7252101B, ATC probe , integral electrode holder & power adapter	
ECPHTUTOR-I	CyberScan pH Tutor Meter with indigenous glass pH electrode AN-786-1 , BNC connector, 1m cable length, indigenous electrode stand and power adapter. ATC probe to be ordered separately	
ECPHTUTOR-D	CyberScan pH Tutor Meter with Plastic-body "3-in-1" pH/Temp.(ATC in-built) Combination Electrode, 12x90mm, BNC connector, 1m cable length, indigenous electrode stand and	

	power adapter	
ECPHTUTOR-S	CyberScan pH Tutor Meter with single junction pH electrode ECFC7252101B , 12x90mm, BNC connector, 1m cable length, indigenous electrode stand and power adapter. ATC probe to be ordered separately	
ECPHTUTOR-DS	CyberScan pH Tutor Meter with Plastic-body "3-in-1" pH/Temp.(ATC in-built) Combination Electrode, 12x90mm, BNC connector, 1m cable length, Integrated Electrode Stand with Swivel Arm and power adapter	



Accessories		
EC620130	Glass body, refillable, open pore (10ml electrolyte 620-430 included)	
ECPH5TEMB01P	ATC Probe (for Tutor, Ion 510, pH 510, pH 700, Ion 700, pH 1100, pH 2100, pH 2700, & Ion 2700), 1m cable length	
ECFG7370101B	Glass body double junction Ag/AgCl refillable pH electrode, 12 x 110 mm, BNC connector, 1m cable (for pH 2700, PC 2700, Ion 2700)	
ECFC7252101B	General Purpose Plastic-body Single Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 1m cable length	
ECFG7350401B	General Purpose Glass-body Single Junction Refillable pH Combination Electrode, annular ceramic reference junction with protective sensor guard, 12x110mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
AN-786-1	General Purpose glass-body Refillable Indigenous pH Combination Electrode, BNC connector, 1m cable length, Brand Antech	
AN-ST-770	Indian Electrode stand, Brand Antech	
ECPHELSTDC	Electrode Stand with Swivel Arm	
ECELSTDCNEW	Electrode Stand with Swivel Arm (for pH Tutor)	
01 X 321801	Electrode Stand with ACCUFLEX Arm (for 700 and 2700 series)	
60X030130	100 /240VAC SMPS Power Adapter with US/UK/EUR/Japan plug ,9V,6W, CENTRE +ve (for Cyberscan Tutor, 11 / 110 /510/ 700/1100 / 2100 series)	
60X030131	100 /240VAC SMPS Power Adapter with US/UK/EUR/Japan plug ,12V,6W, CENTRE -ve (for Cyberscan 1500 series)	
60X426401	100 /240VAC SMPS Power Adapter , 9V,6W (150, 450 and 2700 series)	
ECFC72522R01B	General Purpose Plastic-body Double Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC7352901B	General Purpose Plastic-body "3-in-1" pH/Temp. Combination Electrode, 12x90mm, BNC connector, 1m cable length (for pH 5/6, Ion 6, pH 11/110, pH 510 & pH 1100/2100)	
ECFC7960201B	General Purpose Plastic-body Double Junction Gel-Filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	
AN-270	Dot Matrix Printer, Brand Antech	

Specialty pH Electrodes

ECFG7350401B	General Purpose Glass-body Single Junction Refillable pH Combination Electrode, annular ceramic reference junction	
--------------	--	--

	with protective sensor guard, 12x110mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFG7451901B	Glass-body pH Combination Electrode, reference Ag/AgCl Sealed , 12x110mm, BNC connector, 1m cable length .Ideal for High temp. measurements and photographic samples	
ECFG6350601B	Glass-body pH Combination Electrode, reference Ag/AgCl Refillable , 8x55mm, BNC connector, 1m cable length .Ideal for High viscosity solutions such as emulsions, suspensions, paints and varnishes where frequent cleaning of the reference is necessary, aqueous pH measurements. Quality control, general laboratory and aquarium water	
ECFG6351101B	Glass-body pH Combination Electrode, reference Ag/AgCl Sealed , 8x55mm, BNC connector, 1m cable length .Ideal for Solid or semi-solid samples such as cheese, meats, fruits, bread, or other similar sample	
ECFG7351101B	Glass-body pH Combination Electrode, reference Ag/AgCl Refillable , 12x110 mm, BNC connector, 1m cable length .Ideal for High viscosity solutions such as emulsions, suspensions, paints and varnishes where frequent cleaning of the reference is necessary	
ECFG4390401B	Glass-body pH Combination Micro-Electrode, reference Calomel Refillable ,4x55 mm, BNC connector, 1m cable length .Ideal for Micro sample, such as semi-micro cuvettes and NMR tube, Research measurements, fruit juices, beer, milk and yogurt,Tris buffers, clinical, and biological media containing proteins, creams, fats and cosmetics	
ECFG7252001B	General Purpose, Flat-surface, Glass-body Single Junction Refillable pH Combination Electrode, 12x110mm, BNC connector, 1m cable length. Used for surface measurements such as paper, skin, textile, leather, agar	
EC620185	Glass-body pH Combination Electrode, reference double junction ,Ag/AgCl Refillable , 10x102 mm, BNC connector, 1m cable length .Ideal for Tris buffers, clinical, and biological media containing proteins, creams, fats,Rugged use; ruggedized electrode tip, Aqueous media, Reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides,and cyanides. T Rugged use; ruggedized electrode tip. Aqueous media in general	
EC620130	Glass body, refillable, open pore ,reference double junction ,Ag/AgCl Refillable,12x160 mm, BNC connector, 1m cable length(10ml electrolyte 620-430 included).Ideal for Tris buffers, clinical, and biological media containing proteins, creams, fats,Reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides,and cyanides , Aqueous media in general,Low ionic strength solutions, such as high purity water	
EC620131	Glass-body pH Combination Electrode, reference double junction ,Ag/AgCl Sealed , 12x120 mm, BNC connector, 1m cable length .Ideal for Tris buffers, clinical, and biological media containing proteins, creams, fats,Reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides,and cyanides , Aqueous media in general,High viscosity solutions such as emulsions, suspensions, paints and varnishes where frequent cleaning of the reference is necessary	
EC620132	Plastic-body pH Combination Electrode, reference double junction ,Ag/AgCl Sealed , 12x105 mm, BNC connector, 1m cable length .Ideal for Tris buffers, clinical, and biological media	



	containing proteins, creams, fats,Reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides,and cyanides , Aqueous media in general,Low ionic strength solutions, such as high purity water	
EC620133	Glass body pH combination, polymer, spear tip, double pore Electrode, reference double junction ,Ag/AgCl Sealed , 6 x 80 mm, BNC connector, 1m cable length .Ideal for Solid or semi-solid samples such as cheese, meats, fruits, bread, or other similar sample ,Tris buffers, clinical, and biological media containing proteins, creams, fats,Reference contamination problems which require a double junction reference, such as media containing sulfides, bromides, iodides,and cyanides , Aqueous media in general	
ECFC7252101B	General Purpose Plastic-body Single Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC7252201B	General Purpose Plastic-body Double Junction Gel-Filled pH Combination Electrode, 12X90mm, BNC connector, 1m cable length	
ECFC72521R01B	General Purpose Plastic-body Single Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC72522R01B	General Purpose Plastic-body Double Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	

"3-in-1" pH/Temp Electrodes

ECFC7352901B	General Purpose Plastic-body "3-in-1" pH/Temp. Combination Electrode, 12x90mm, BNC connector, 1m cable length (for pH 5/6, Ion 6, pH 11/110, pH 510 & pH 1100/2100)	
ECFC7352901W	General Purpose Plastic-body Gel-Filled "3-in-1" pH/Temp. Combination Electrode, 12x90mm, BNC and 6 pin connector, 1m cable length (for pH 310, 300, PC300 & PC510)	

ORP Electrodes

ECFG7960101B	General Purpose Glass-body Single Junction Refillable ORP Electrode, 12x110mm, BNC connector, 1m cable length	
ECFC7960101B	General Purpose Plastic-body Single Junction Gel-Filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC7960201B	General Purpose Plastic-body Double Junction Gel-Filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	

Ion Selective Electrodes (U.S.A Make)

Epoxy body, Flush Reference Combined & Epoxy sealed

Ammonia (NH ₃)Ion Electrode	Ammonia Gas Sensor	
Ammonium (NH ₄ ⁺)Ion Electrode	Ammonium Combination	
Bromide (Br ⁻) Ion Electrode	Bromide Combination	
Cadmium (Cd ⁺²) Ion Electrode	Cadmium Combination	
Calcium (Ca ⁺²) Ion Electrode	Calcium Combination	

Carbon Dioxide (CO ₂) Ion Electrode	Carbon Dioxide Gas Sensor	
Chloride (Cl ⁻) Ion Electrode	Chloride Combination	
Copper (Cu ⁺²) Ion Electrode	Copper Combination	
Cyanide (CN ⁻) Ion Electrode	Cyanide Combination	
Fluoride (F ⁻) Ion Electrode	Fluoride Combination	
Fluoroborate (BF ₄ ⁻) Ion Electrode	Fluoroborate Combination	
Iodide (I ⁻) Ion Electrode	Iodide Combination	
Lead (Pb ⁺²) Ion Electrode	Lead Combination	
Nitrate (NO ₃ ⁻) Ion Electrode	Nitrate Combination	
Nitrogen Oxide (NO _x) Ion Electrode	Nitrogen Oxide Combination	
Perchlorate (ClO ₄ ⁻) Ion Electrode	Perchlorate Combination	
Potassium (K ⁺) Ion Electrode	Potassium Combination	
Silver (Ag ⁺) Ion Electrode	Silver Combination	
Sodium (Na ⁺) Ion Electrode	Sodium Combination	
Sulfide (S ⁻²) Ion Electrode	Sulfide Combination	
Surfactant (X ⁺ /X ⁻) Ion Electrode	Surfactant Combination	
Water Hardness (Ca ⁺² /Mg ⁺²) Ion Electrode	Water Hardness Combination	

Note: All ISEs come with 1-meter cable length and BNC type connector

Calibration Standards And ISA For Ion Selective Electrodes (Indigenous, Brand Antech)

Ammonia Ion Electrode Solutions





AM-CAL1S	Standard 0.1M (500 ml)	
AM-CAL2S	Standard 1000 ppm (500 ml)	
AM-CAL3S	Standard 100 ppm (500 ml)	
AM-ISA1S	Ionic Strength Adjuster (500 ml)	
Ammonium Ion Electrode Solutions		
AMM-CAL1S	Standard 0.1M (500 ml)	
AMM-CAL2S	Standard 1000 ppm (500 ml)	
AMM-CAL3S	Standard 100 ppm(500 ml)	
AMM-ISA1S	Ionic Strength Adjuster(500 ml)	
Bromide Ion Electrode Solutions		
BR-CAL1S	Standard 0.1M (500 ml)	
BR-CAL2S	Standard 1000 ppm (500 ml)	
BR-ISA1S	Ionic Strength Adjuster (500 ml)	
Cadmium Ion Electrode Solutions		
CD-CAL1S	Standard 0.1M (500 ml)	
CD-CAL2S	Standard 1000 ppm (500 ml)	
CD-ISA1S	Ionic Strength Adjuster (500 ml)	
Calcium Ion Electrode Solutions		
CA-CAL1S	Standard 0.1M (500 ml)	
CA-CAL2S	Standard 1000 ppm (500 ml)	
CA-CAL3S	Standard 100 ppm (500 ml)	
CA-ISA1S	Ionic Strength Adjuster(500 ml)	
Carbon Dioxide Ion Electrode Solutions		
CO-CAL1S	Standard 0.1M (500 ml)	
CO-CAL2S	Standard 1000 ppm (500 ml)	
CO-CAL3S	Standard 100 ppm(500 ml)	
CO-ISA1S	Ionic Strength Adjuster(500 ml)	
Chloride Ion Electrode Solutions		
CL-CAL1S	Standard 0.1M (500 ml)	
CL-CAL2S	Standard 1000 ppm (500 ml)	
CL-CAL3S	Standard 100 ppm (500 ml)	
CL-ISA1S	Ionic Strength Adjuster(500 ml)	
Copper Ion Electrode Solutions		
CU-CAL1S	Standard 0.1M (500 ml)	
CU-CAL2S	Standard 1000 ppm (500 ml)	
CU-ISA1S	Ionic Strength Adjuster (500 ml)	
Fluoride Ion Electrode Solutions		
FL-CAL1S	Standard 0.1M (500 ml)	

FL-CAL2S	Standard 1000 ppm (500 ml)	
FL-CAL3S	Standard 100 ppm(500 ml)	
FL-ISA1S	Ionic Strength Adjuster(500 ml)	
FL-ISA2S	Ionic Strength Adjuster(500 ml) (Low Concentration)	
Fluoroborate Ion Electrode Solutions		
FB-CAL2S	Standard 1000 ppm (500 ml)	
FB-CAL3S	Standard 100 ppm(500 ml)	
FB-ISA1S	Ionic Strength Adjuster(500 ml)	
Lead Ion Electrode Solutions		
PB-CAL1S	Standard 0.1M (500 ml)	
PB-CAL2S	Standard 1000 ppm (500 ml)	
PB-ISA1S	Ionic Strength Adjuster (500 ml)	
Nitrate Ion Electrode Solutions		
NT-CAL1S	Standard 0.1M (500 ml)	
NT-CAL2S	Standard 1000 ppm (500 ml)	
NT-CAL3S	Standard 100 ppm(500 ml)	
NT-ISA1S	Ionic Strength Adjuster (500 ml)	
Perchlorate Ion Electrode Solutions		
PC-CAL2S	Standard 1000 ppm (500 ml)	
PC-ISA1S	Ionic Strength Adjuster (500 ml)	
Potassium Ion Electrode Solutions		
KO-CAL1S	Standard 0.1M (500 ml)	
KO-CAL2S	Standard 1000 ppm (500 ml)	
KO-ISA1S	Ionic Strength Adjuster(500 ml)	
Silver / Sulfide Ion Electrode Solutions		
SS-CAL1S	Standard 0.1M (500 ml)	
SS-CAL2S	Standard 1000 ppm (500 ml)	
SS-ISA1S	Ionic Strength Adjuster(500 ml)	
Surfactant Ion Electrode Solutions		
SF-CAL2S	Standard 1000 ppm (500 ml)	
SF-ISA1S	Ionic Strength Adjuster(500 ml)	
Sodium Ion Electrode Solutions		
NA-CAL1S	Standard 0.1M (500 ml)	
NA-CAL2S	Standard 1000 ppm (500 ml)	
NA-CAL3S	Standard 100 ppm(500 ml)	
NA-ISA1S	Ionic Strength Adjuster(500 ml)	
Iodide Ion Electrode Solutions		
IO-CAL1S	Standard 0.1M (500 ml)	

IO-CAL2S	Standard 1000 ppm (500 ml)	
IO-CAL3S	Standard 100 ppm(500 ml)	
IO-ISA1S	Ionic Strength Adjuster(500 ml)	
Water Hardness Ion Electrode Solutions		
WH-CAL2S	Standard 1000 ppm (500 ml)	
WH-CAL3S	Standard 100 ppm (500 ml)	
WH-ISA1S	Ionic Strength Adjuster(500 ml)	

Note: Calibration standards of specific strength can be provided on request

Waterproof Conductivity / TDS / Salinity Pocket Testers

ECOECTESTLOW	Waterproof EcoTestr EC Low Tester with ATC, 1 point Calibration	
ECOECTESTHIGH	Waterproof EcoTestr EC High Tester with ATC; 1 point Calibration	
		
ECTEST11	Waterproof ECTestr11 Dual Range Tester with ATC & temperature display (0 - 2000 μ S/cm; 0 -20.00 mS/cm)	
ECTEST11PLS	Waterproof ECTestr11+ Multi Range Tester with ATC & temperature display (0 - 200.0 μ S/cm; 0 - 2000 μ S/cm; 0 - 20.00 mS/cm)	
		
ECOTDSTESTLOW	Waterproof EcoTestr TDS Low Tester with ATC, 1 point Calibration	
ECOTDSTESTHIGH	Waterproof EcoTestr TDS High Tester with ATC; 1 point Calibration	
		
TDSTEST11	Waterproof TDSTestr11 Dual Range Tester with ATC & temperature display (0 - 1000 ppm; 0 -10.00 ppt)	
TDSTEST11PLS	Waterproof TDSTestr11+ Multi Range Tester with ATC & temperature display (0 - 100.0 ppm; 0 -1000 ppm; 0 - 10.00 ppt)	
		
SALTTEST11	Waterproof SaltTestr11 Tester with ATC & temperature display (0 - 10.00 ppt)	

Accessories

ECTDSENSORPLUS	Replacement Sensor for ECTestr10+,TDSTestr10+ Series & ECTestr11+, TDSTestr11+, Cup type	
ECTDSENSOR	Replacement Sensor for ECTestr, ECTestr10, TDSTestr, TDSTestr10 Series, ECTestr11, TDSTestr11 & all SaltTestr Series, 2-pin type	

Economy Conductivity / TDS / Salinity Handheld Meters

ECCON603PLUSK	COND 6+ Conductivity Meter with electrode CONSEN91B & Conductivity carrying kit set	
ECTDS603PLUSK	TDS 6+ TDS Meter with electrode CONSEN91B & TDS carrying kit set	

ECSALT603PLUSK	Salt 6+ Salinity Meter with electrode CONSEN91B & Salinity carrying kit set	
----------------	---	--

Remove Watermark Now

Waterproof Conductivity / TDS / Salinity Handheld Meters

ECCONWP15003K	CON 150 Meter Kit: Meter, conductivity cell CONSEN91W (K = 1.0), Grip-Clip™, two AA batteries, hard carry case, calibration solutions	
ECCONWP45003K	CON 450 Meter Kit: Meter, conductivity cell ,CONSEN91W (K = 1.0), Grip-Clip™, two AA batteries, hard carry case, USB cable, calibration solutions	



Waterproof Conductivity / TDS / Salinity /Resistivity Handheld Meters

ECCONWP61043K	Waterproof CyberScan CON 610 Conductivity/TDS/ Resistivity/Salinity Meter with 3m cable 4-cell electrode CONSEN9203J K=0.530, DAS software, power adapter & Conductivity/TDS carrying kit set	
ECCONWP60043K	Waterproof CyberScan CON 600 Conductivity/TDS Meter with 3m cable 4-cell electrode CONSEN9203J K=0.530, DAS software, power adapter & Conductivity/TDS carrying kit set	

Accessories

CONSEN91B	2 Stainless Steel Rings Ultem-body Electrode with ATC, cell constant K=1.0, 16x144 mm, BNC connector, 1m cable length (for CON 6+, TDS 6+, SALT 6+)	
CONSEN91W	2 Stainless Steel Rings Ultem-body Electrode with ATC, cell constant K=1.0, 16x144 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510 & PC 510 ,CON 150, CON 450, PC 450)	
CONSEN9203J	4 Cell Bulls-Eye Epoxy-body Electrode with ATC, K=0.530 12x120 mm, 8-pin connector, 3m cable length (for COND600, COND610, PC650, PCD650)	
ECECOCONKIT	Economy Conductivity/TDS Carrying Kit Set – Plastic Carrying Case comprises: 1 x 1413 uS, 12.88 mS KCl and 3000 ppm 442 standard solutions and 1 x deionised rinse water (60 ml)	
ECCONWPKIT	CyberScan Conductivity/TDS Carrying Kit Set – Plastic Carrying Case comprises: 1 x 1413 mS, 12.88 mS KCl, 3000 ppm 442 standard solutions and 1 x deionised rinse water (60 ml)	
ECCONWP600KIT	CyberScan CON 600 Series Carrying Kit Set – Plastic Carrying Case comprises: 1 x 1413 uS, 12.88 mS KCl, 3000 ppm 442 standard solutions and 1 x deionised rinse water (60 ml)	
01X030132	Universal SMPS,100 /240VAC,9V,6W, CENTRE +ve Power Adapter with US/UK/EUR/Japan plug (for Cyberscan 600 series)	
60X030130	100 /240VAC SMPS Power Adapter with US/UK/EUR/Japan plug ,9V,6W, CENTRE +ve (for Cyberscan 11 / 110 / 1100 / 2100 series)	
60X426401	100 /240VAC SMPS Power Adapter , 9V,6W (150, 450 and 2700 series)	
01X447602	USB / IrDA Interface Adapter (for 600 Series Meter to PC Communication)	
CONSEN72W	2 stainless steel rings glass- body electrode with ATC, cell constant K=0.1, 16x110 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510))	

CONSEN92W	2-Cell Conductivity/ATC Electrode, 10.0 cell constant, Platinum Sensor, Epoxy-Body (150 / 450 series)	
CONSEN73W	2 Platinum Rings Epoxy-body Electrode with ATC, cell constant K=10.0, 16x110 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, CON 510)	
CONSEN9103J	2 Stainless Steel Rings Ultem-body Electrode with ATC, cell constant K=1.0, 16x144 mm, 8-pin connector, 3m cable length (for COND600, COND610, PC650, PCD650)	
ECCONSEN93J	2 Cell Electrode with ATC, cell constant K=0.1 , 16x110 mm, 8-pin connector, 1m cable length (for CON600, COND610, PC650, PCD650)	

Conductivity / TDS / Salinity / Resistivity Bench Meters



ECCON70043S	Eutech CON 700 Meter With Conductivity/ATC Probe CONSEN9501D ,K=1.0 , Integral Electrode Holder & 100/240 VAC Adapter	
ECCON270043S	Eutech CON 2700 Meter With 4-Cell Conductivity Probe CONSEN9201D K=0.530, Integral Electrode Holder & 100/240 VAC Adapter, RS232 cable	

Accessories

CONSEN91W	2 Stainless Steel Rings Ultem-body Electrode with ATC, cell constant K=1.0, 16x144 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510 & PC 510 ,CON 150, CON 450, PC 450)	
CONSEN72W	2 stainless steel rings glass- body electrode with ATC, cell constant K=0.1, 16x110 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510)	
CONSEN73W	2 Platinum Plates Epoxy-body Electrode with ATC, cell constant K=10.0, 16x110 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510)	
93X546101	2-Cell Conductivity/ATC Electrode, 0.1 cell constant, SS Sensor, Epoxy-Body (700 & 2700 series)	
CONSEN9201D	4-Cell Conductivity/ATC Electrode K=0.530, Graphite Sensor, Epoxy-Body (2700 series)	
CONSEN9501D	2-Cell Conductivity/ATC Electrode K=1.0, stainless steel sensor, Ultem-body (700 or 2700 series)	
60X030131	100 /240VAC SMPS Power Adapter with US/UK/EUR/Japan plug ,12V,6W, CENTRE -ve (for Cyberscan 1500 series)	
252757-001	100 /240VAC SMPS Power Adapter , 9V,6W (for 2700 series)	

Economy Dissolved Oxygen Handheld Meter

ECDO602PLUSK	Galvanic Dissolved Oxygen Meter with 3m cable electrode , 2 assembled membrane cap housing, 1 refilling electrolyte (10ml) & carrying kit set	
--------------	---	--



Waterproof Dissolved Oxygen Handheld Meters : RDO technology



ECDOWP45003K	DO 450 meter Kit, RDO electrode with sensor cap RDO3M, two AA batteries, hard carry case, USB cable, RDO stainless steel weight/guard, RDO calibration chamber	
--------------	--	--

Waterproof Dissolved Oxygen Handheld Meters

ECDOWP60041K	Waterproof CyberScan DO 600 Dissolved Oxygen Meter with 10 ft cable electrode ECDOHANDYNEW, DAS software, power adapter & carrying kit set	
--------------	--	--

Accessories

ECDO6HANDY3M	Galvanic Dissolved Oxygen Electrode with ATC, 3m cable length (for DO 6)	
ECDO6HANDY	Galvanic Dissolved Oxygen Electrode with ATC, 1m cable length (for DO 6)	
ECDOHANDYNEW	Galvanic Dissolved Oxygen Electrode with ATC, 10 ft cable length , 1 assembled membrane cap housing, 1 refilling electrolyte (60ml) and 1 scouring pad (for DO110, DO 300, PD 300, DO600, PD650, CD650, PCD650)	

Accessories

01X211226	DO Refilling Electrolyte (60 ml) (for DO 6, DO100, DO110, DO 300, PD 300, DO 600, CD 650, PD 650 & PCD 650)	
01X241608	Assembled Membrane Cap Housing for ECDO6HANDY & ECDO6HANDY3M (1 unit) (for DO 6)	
01X623901	Assembled Membrane Cap Housing (for DO100, DO110, DO 300 & PD 300)	
01X241603	Membranes & O-rings (Pack of 5 units) (for DO100, DO110, DO 300 & PD 300)	
15X241502	Tool for ECDOHANDYNEW membrane housing	
ECDOZEROSOLN	Zero Oxygen Solution, 0 % DO, 480 ml	
ECWP600DRYKIT	CyberScan DO 600 Series Carrying Kit Set – Plastic Carrying Case comprises: 4 empty bottles (60 ml)	
60X030130	100 /240VAC SMPS Power Adapter with US/UK/EUR/Japan plug ,9V,6W, CENTRE +ve (for Cyberscan 11 / 110 / 1100 / 2100 series)	
01X030132	Universal SMPS,100 /240VAC,9V,6W, CENTRE +ve Power Adapter with US/UK/EUR/Japan plug (for Cyberscan 600 series)	
60X426401	100 /240VAC SMPS Power Adapter , 9V,6W (150, 450 and 2700 series)	
01X447602	USB / IrDA Interface Adapter (for 600 Series Meter to PC Communication)	
RDOCAP	Replacement RDO cap	
RDO3M	RDO probe 3 M / 10 ft	
RDO6M	RDO probe 6 M / 20 ft	

RDO15M	RDO probe 15 M / 50 ft	
RDOCALCHAMBER	RDO Calibration Chamber	
RDOWEIGHT	RDO Weight	

Dissolved Oxygen Bench Meters

ECDO70042S	Eutech DO 700 Meter With Dissolved Oxygen/ATC Probe (01X233913), Integral Electrode Holder & 100/240 VAC Adapter	
ECDO270042	DO 2700 Meter With Self-Stirring Dissolved Oxygen / BOD Electrode (EC620SSP), RS232C Cable & 100/240 VAC Adapter, RS232 cable	

Accessories

252757-001	100 /240VAC SMPS Power Adapter , 9V,6W (for 2700 series)	
EC620SSP	DO/BOD electrode with self-stirring mechanism, 1m cable length	
ECDOZEROSOLN	Zero Oxygen Solution, 0 % DO, 480 ml	

Waterproof Multi-Parameter Pocket Testers



EXPERTCTS	Waterproof Expert CTS Conductivity/TDS/salinity pocket tester with ATC and temperature display (0.00-20.00mS/cm; 0.00 -20.00 ppt; 0.0 -10.0 ppt)	
PCTEST35	Waterproof PCTestr 35 pH/Conductivity/Temp Tester with ATC; (± 0.1 pH resolution; 0 - 2000 μ S/cm; 0 - 20.00 mS/cm)	
PTTEST35	Waterproof PTTestr 35 pH/TDS/Temp Tester with ATC; (± 0.1 pH resolution; 0 - 1000 ppm; 0 - 10.00 ppt)	
PCSTEST35	Waterproof PCSTestr 35 pH/Conductivity/TDS/Salinity/Temp Tester with ATC; (± 0.01 pH resolution; 0 - 200.0 μ S/cm; 0 - 2000 μ S/cm; 0 - 20.00 mS/cm; 0 - 100.0 ppm; 0 - 1000 ppm; 0 - 10.00 ppt; 0 - 100.0 ppm; 0 - 1000 ppm; 0 - 10.00 ppt; 0 - 1.00%)	



Accessories

PCSENSOR	Replacement pH/Conductivity/Temp Sensor for PCTestr 35, PTTestr 35, PCSTestr 35	
----------	---	--

Waterproof Multi-Parameter Handheld Meters Handheld Meters

ECPCWP45004K	PC 450 Meter with separate pH & cond probes Kit with double-junction pH electrode ECFC7252201B, conductivity cell CONSEN91W (K = 1.0) , Grip-Clip™, two AA batteries, hard carry case, USB cable and calibration solutions	
ECPDWP45004K	PD 450 Meter Kit: Meter, pH electrode ECDA9350603B, RDO electrode with sensor cap RDO3M, two AA batteries, hard carry case, USB cable, RDO stainless steel weight/guard, RDO	

Waterproof Multi-Parameter Handheld Meters

	ECPCWP65043K Waterproof CyberScan PC 650 pH/ mV/ Ion/ Conductivity/ TDS/ Resistivity/ Salinity Meter with double junction pH electrode ECFC7252203B, 4-cell Conductivity probe CONSEN9203J, DAS software, multi-probe holder, power adapter & carrying kit set (all probes comes with 3m long cable).	
Note: PC 650 pH/Conductivity Carrying Kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, 1 x 12.88 mS KCl standard solution and 1 x deionised (rinse) water (60 ml each)		
	ECCDWP65043K Waterproof CyberScan CD 650 Conductivity/ TDS/ Resistivity/ Salinity/ Dissolved Oxygen Meter with 4-cell Conductivity probe CONSEN9203J, Dissolved Oxygen probe ECDOHANDYNEW, DAS software, multi-probe holder, power adapter & carrying kit set (all probes comes with 3m long cable)	
Note: CD 650 Conductivity/DO Carrying Kit consists of a carrying case with 1 x 1413 uS, 12.88 mS KCl, 3000 ppm standard solutions and 1 x deionised (rinse) water (60 ml each)		
	ECPDWP65043K Waterproof CyberScan PD 650 pH/ mV/ Ion/ Dissolved Oxygen Meter with double junction pH electrode ECFC7252203B, ATC probe ECPHWPTM03J, Dissolved Oxygen probe ECDOHANDYNEW, DAS software, multi-probe holder, power adapter & carrying kit set (all probes comes with 3m long cable).	
Note: PD 650 pH/DO Carrying Kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, 1 x Storage solution and 1 x deionised (rinse) water (60 ml each)		
	ECPCDWP65044K Waterproof CyberScan PCD 650 pH/ mV/ Ion/ Conductivity/ TDS/ Resistivity/ Salinity/ Dissolved Oxygen Meter with double junction pH electrode ECFC7252203B, 4-cell Conductivity probe CONSEN9203J, Dissolved Oxygen probe ECDOHANDYNEW, DAS software, multi-probe holder, power adapter & carrying kit set (all probes comes with 3m long cable).	
Note: PCD 650 pH/Conductivity/DO Carrying Kit consists of a carrying case with 1 x pH 4.01, pH 7.00 buffer solutions, 1 x 12.88 mS KCl standard solution and 1 x deionised (rinse) water (60 ml each)		

Accessories

ECFC7252201B	General Purpose Plastic-body Double Junction Gel-Filled pH Combination Electrode, 12X90mm, BNC connector, 1m cable length	
CONSEN91W	2 Stainless Steel Rings Ultem-body Electrode with ATC, cell constant K=1.0, 16x144 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510 & PC 510 ,CON 150, CON 450, PC 450)	
CONSEN92W	2-Cell Conductivity/ATC Electrode, 10.0 cell constant, Platinum Sensor, Epoxy-Body (150 / 450 series)	
ECDOHANDYNEW	Galvanic Dissolved Oxygen Electrode with ATC, 3 m cable length , 1 assembled membrane cap housing, 1 refilling electrolyte (60ml) and 1 scouring pad (for DO110, DO 300, PD 300, DO600, PD650, CD650, PCD650)	
ECPHWPTM03J	ATC Probe (for pH 620, 610, 600, PC650, PD650, PCD650 only); 3m cable length	
ECFC7252203B	General Purpose Plastic-body Double Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 3m cable length	

CONSEN9203J	4 Cell Bulls-Eye Epoxy-body Electrode with ATC, 12x120 mm, 8-pin connector, 3m cable length (for COND600, COND610, PC650, PCD650)	
ECPCWPKIT	pH/Conductivity Kit Set – Plastic Carrying Case comprises: 1 x pH 4.01, pH 7.00 buffer solution 1 x 1413 uS, 12.88 mS KCl standard solution (60 ml each)	
ECPHWPKIT	CyberScan pH Carrying Kit Set - Plastic Carrying Case comprises: 1 x pH 4.01, pH 7.00 buffer solutions, storage solution and 1 x deionised (rinse) water (60 ml each)	
ECPCWP650KIT	pH/Conductivity Kit Set – Plastic Carrying Case comprises: 1 x pH 4.01, pH 7.00 buffer solution 1 x 12.88 mS KCl standard solution and 1 x deionised (rinse) water (60 ml each) (for PC650 & PCD650)	
60X426401	100 /240VAC SMPS Power Adapter , 9V,6W (150, 450 and 2700 series)	
01X623901	Assembled Membrane Cap Housing (for DO100, DO110, DO 300 & PD 300)	
01X211226	DO Refilling Electrolyte (60 ml) (for DO 6, DO100, DO110, DO 300, PD 300, DO 600, CD 650, PD 650 & PCD 650)	
01X241603	Membranes & O-rings (Pack of 5 units) (for DO100, DO110, DO 300 & PD 300)	
01X030132	Universal SMPS,100 /240VAC,9V,6W, CENTRE +ve Power Adapter with US/UK/EUR/Japan plug (for Cyberscan 600 series)	
01X447602	USB / IrDA Interface Adapter (for 600 Series Meter to PC Communication)	
PHWPTEM01W	ATC Probe ATC Probe (for pH 310, pH 300, PC300 ,PC510, PH 150, CON 150, PH 450, CON 450, PC 450) 1m cable length	
ECPHWPTM01J	ATC Probe (for pH 620, 610, 600, PC650, PD650, PCD650 only); 1m cable length	
ECFC72522R01B	General Purpose Plastic-body Double Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC7352901W	General Purpose Plastic-body Gel-Filled “3-in-1” pH/Temp. Combination Electrode, 12x90mm, BNC and 6 pin connector, 1m cable length (for pH 310, 300, PC300 & PC510)	
ECFC7352901J	General Purpose Plastic-body Gel-Filled “3-in-1” pH/Temp. Combination Electrode, 12x90mm, BNC and 8 pin connector, 1m cable length (for pH 620, 610, 600, PC650, PD650, PCD650 only)	
CONSEN9103J	2 Stainless Steel Rings Ultem-body Electrode with ATC, cell constant K=1.0, 16x144 mm, 8-pin connector, 3m cable length (for COND600, COND610, PC650, PCD650)	
ECCONSEN93J	2 Cell Electrode with ATC, cell constant K=0.1 , 16x110 mm, 8-pin connector, 1m cable length (for CON600, COND610, PC650, PCD650)	

Multi-Parameter Bench Meters

ECPC70043S	PC 700 Meter With pH Electrode (ECFC7252101B), Conductivity/ATC Probe (CONSEN9501D), Integral Electrode Holder & 100/240 VAC Adapter	
ECPC270043S	PC 2700 Meter With pH Electrode (ECFG7370101B), 4-Cell Conductivity/ATC Electrode, Graphite Sensor, Epoxy-Body(CONSEN9201D), Integral Electrode Holder & 100/240 VAC Adapter, RS232 cable, & pH Electrode Refill Solution	



Accessories		
EC620130	Glass body, refillable, open pore (10ml electrolyte 620-430 included)	
ECFC7252201B	General Purpose Plastic-body Double Junction Gel-Filled pH Combination Electrode, 12x90mm, BNC connector, 1m cable length	
CONSEN91W	2 Stainless Steel Rings Ultem-body Electrode with ATC, cell constant K=1.0, 16x144 mm, 6-pin connector, 1m cable length (for CON 110 , CON 11, CON 410 , CON 400, PC 300, CON 510 & PC 510 ,CON 150, CON 450, PC 450)	
PHWPTEM01W	ATC Probe ATC Probe (for pH 310, pH 300, PC300 ,PC510, PH 150, CON 150, PH 450, CON 450, PC 450) 1m cable length	
ECFC7352901W	General Purpose Plastic-body Gel-Filled "3-in-1" pH/Temp. Combination Electrode, 12x90mm, BNC and 6 pin connector, 1m cable length (for pH 310, 300, PC300 & PC510)	
ECFC72522R01B	General Purpose Plastic-body Double Junction Refillable pH Combination Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFG7350401B	General Purpose Glass-body Single Junction Refillable pH Combination Electrode, annular ceramic reference junction with protective sensor guard, 12x110mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
ECFC7960201B	General Purpose Plastic-body Double Junction Gel-Filled ORP Electrode, 12x90mm, BNC connector, 1m cable length	
ECFC79602R01B	General Purpose Plastic-body Double Junction Refillable ORP Electrode, 12x90mm, BNC connector, 1m cable length & 10ml refilling electrolyte	
CONSEN9201D	4-Cell Conductivity/ATC Electrode K=0.530, Graphite Sensor, Epoxy-Body (2700 series)	
CONSEN9501D	2-Cell Conductivity/ATC Electrode K=1.0, stainless steel sensor, Ultem-body (700 or 2700 series)	
93X546101	Electrode, Conductivity, K=0.1, Platinum, 12mm x 110mm, 30K Thermistor, 8 pin din (CON 700 / PC 700 / CON 2700 / PC 2700)	
252757-001	100 /240VAC SMPS Power Adapter , 9V,6W (for 2700 series)	



Waterproof Turbidity Portable Meter		
ECTN100IR	Waterproof TN-100 handheld turbidity meter with set of 4 calibration standards (800, 100, 20.0 & 0.02 NTU), sample vials, lint-free cloth, silicone oil, batteries, and hard carrying case	

Accessories		
TN100CALKIT	Calibration Kit Set for TN100IR (0.02, 20.0, 100, 800 NTU) , 4 x 60 ml	
ECTN100CUVKIT	Pack of 3 Sample Cuvettes (TN100IR)	
ECTN100CUVKIT4	Pack of 4 Sample Cuvettes (TN100IR)	
ECSILICONEOIL	Silicone Oil (10 ml) for TN100IR	
01X344318	10.0 NTU Calibration Standard (125 mL)	
60X030133	SMPS Power Adapter, 15V/1A (TB 1000 series)	
ECPORRHASSY	Pour through Assembly for TB1000	

ECTNGSTNLMP	Tungsten Filament lamp module (white light)	
ECINFRDLMP	Infra Red lamp module	
ECTBDCUV03KT	Pack of 3 sample cuvettes	
ECBATT3032	Internal Batteries (pack of 2)	
ECMICRO100CBL	Customized RS232 Cable for TB 1000 Meter Series to Serial Printer	

Thermo Scientific Temperature Hand-Held Meters

Thermo Scientific Temp 300 Series Dual-Input Thermocouple Data logging Thermometers

TSTEMP300	Thermo Scientific Temp 300 dual-input thermocouple data logger with rubber armour/stand (Probe Not Included)	
-----------	--	--

Thermo Scientific Temp 10 Series Single-Input J , K, T Type Thermocouple Thermometer

TSTEMP10J	Thermo Scientific Temp 10 Type J Thermocouple Thermometer with Rubber Armour/Stand (Probe Not Included)	
TSTEMP10K	Thermo Scientific Temp 10 Type K Thermocouple Thermometer with Rubber Armour/Stand (Probe Not Included)	
TSTEMP10T	Thermo Scientific Temp 10 Type T Thermocouple Thermometer with Rubber Armour/Stand (Probe Not Included)	



Thermocouple Probes

TPGLPJ01M	Type J General purpose probe (for immersion into liquids), 1m cable length	
TPPENJ01M	Type J Penetration probe (for penetrating meat, plastic and semi-soft materials), 1m cable length	
TPGLPK01M	Type K General purpose probe (for immersion into liquids), 1m cable length	
TPPENK01M	Type K Penetration probe (for penetrating meat, plastic and semi-soft materials), 1m cable length	
TPSURK01M	Type K Surface Straight probe (for direct contact on hot surfaces), 1m cable length	

Thermo Scientific Temp 360 Precision RTD Data logging Thermometer

TSTEMP360	Thermo Scientific RTD Data logger with rubber armour/stand (probe not included)	
-----------	---	--

Thermo Scientific Temp16 Single-Input Precision RTD Thermometer

TSTEMP16	Thermo Scientific Thermistor Thermometer with Rubber Armour / Stand (Probe Not Included)	
----------	--	--

Thermo Scientific Temp14 Single-Input Precision RTD Thermometer

TSTEMP14	Thermo Scientific Temp 14 Thermistor Thermometer (Probe Not Included)	
----------	---	--

Accessories

60X030134	100/240 VAC,9V,6W,CNT-VE, Power Adapter for 300 series	
30X379302	USB Cable for 300 series	

Thermocouple Type K Probes

EC3K220	Type K thermocouple probe with shaft length: 200 mm, round-tip sensor tip: 2 mm diameter; -50 to +700 °C (for liquid/air measurement)	
EC3K320	Type K thermocouple probe with shaft length: 200 mm, round-tip sensor tip: 3.2 mm diameter; -50 to +700 °C (for liquid/air measurement)	
EC3K350	Type K thermocouple probe with shaft length: 500 mm, round-tip sensor tip: 3.2 mm diameter; -50 to +700 °C (for liquid/air measurement)	
EC3K6100	Type K thermocouple probe with shaft length: 1000 mm, round-tip sensor tip: 6 mm diameter; -50 to +1000 °C (for liquid/air measurement)	
EC3K650	Type K thermocouple probe with shaft length: 500 mm, round-tip sensor tip: 6 mm diameter; -60 to +1100 °C (for liquid/air measurement)	
EC3K520C	Type K thermocouple probe with shaft length: 200 mm, flat sensor tip: 5 mm diameter; -60 to +600 °C (for surface contact measurement)	
EC3K1200	Type K thermocouple probe with shaft length: 2000 mm; exposed junction type; -50 to +400°C	

Thermocouple Type T Probes

EC3T320	Type T thermocouple probe with shaft length: 200 mm, round-tip sensor tip: 3.2 mm diameter; -50 to +350 °C (for liquid measurement)	
EC3T415	Type T thermocouple probe with shaft length: 200 mm, penetration sharp sensor tip: 4 mm diameter; -50 to +350 °C (for semi-solid measurement)	
EC3T215	Type T thermocouple probe with shaft length: 150 mm, penetration sharp sensor tip: 2 mm diameter; -50 to +350 °C (for semi-solid measurement)	
EC3T520C	Type T thermocouple probe with shaft length: 200 mm, flat sensor tip: 5 mm diameter; -50 to +350 °C (for surface contact measurement)	
EC3T420A	Type T thermocouple probe with shaft length: 200 mm, sensor tip: 4 mm diameter (for air measurement); -50 to +250 °C	
EC3T210	Type T thermocouple probe with shaft length: 100 mm, penetration sharp sensor tip: 3 mm diameter; -50 to +300 °C (for semi-solid measurement); cable and probe at 300 °C	

RTD Pt 100 Probes

ECPT56L	RTD PT100 probe with shaft length: 200 mm, round-tip sensor tip: 3 mm diameter (for liquid measurement); -50 to +400 °C	
ECPT56C	RTD PT100 probe with shaft length: 200 mm, round-tip sensor tip: 5 mm diameter (for contact measurement); -50 to +400 °C	
ECPT56P	RTD PT100 thermocouple probe with shaft length: 500 mm, penetration sharp sensor tip: 4 mm diameter; ; -50 to +400 °C (for semi-solid measurement)	
ECPT56A	RTD PT100 thermocouple probe with shaft length: 200 mm, sensor tip: 4 mm diameter (for air measurement); -50 to +250 °C	
ECPT56L 1/5 DIN	RTD PT100 thermocouple probe with shaft length: 200 mm, round-tip sensor tip: 3 mm diameter; -50 to +400 °C	
ECPT56 TFE	RTD PT100 thermocouple probe with shaft length: 100 mm, round-tip sensor tip: 4 mm diameter; -50 to +200 °C	



	cable and probe at 300 oC	
ECPT56/500	RTD PT100 thermocouple probe with shaft length: 500 mm, round-tip sensor tip: 6 mm diameter; -50 to +400 °C	
ECPT56/1000	RTD PT100 thermocouple probe with shaft length: 1000 mm, round-tip sensor tip: 6 mm diameter; -50 to +400 °C	
ECTEM6TEM01R	3 wire RTD Pt100 Temperature Probe	

Specialty Meters

ECPHSIMULATOR	Precision Hi-Low Impedance & Multiple Buffers pH Simulator (with BNC-BNC cable provided)	
---------------	--	--

pH/ORP Calibration Standards

pH Buffer Tablets ((Box Of 100 Tablets)

ECBU4BX	pH 4 Buffer Tablets (Box Of 100 Tablets)	
ECBU7BX	pH 7 Buffer Tablets (Box Of 100 Tablets)	
ECBU10BX	pH 10 Buffer Tablets (Box Of 100 Tablets)	

pH Buffer Solutions (480 ml Per Bottle)

ECBU1BT	pH 1.68 Buffer Solution	
ECBU4BTC	pH 4.01 Buffer Solution (Colored)	
ECBU4BT	pH 4.01 Buffer Solution (Colorless)	
ECBU686BT	pH 6.86 Buffer Solution	
ECBU7BTC	pH 7.00 Buffer Solution (Colored)	
ECBU7BT	pH 7.00 Buffer Solution (Colorless)	
ECBU9BT	pH 9.00 Buffer Solution	
ECBU918BT	pH 9.18 Buffer Solution	
ECBU10BTC	pH 10.01 Buffer Solution (Colored)	
ECBU10BT	pH 10.01 Buffer Solution (Colorless)	
ECBU12BT	pH 12.45 Buffer Solution	

pH Buffer Solutions (1 ltr Per Bottle)

ECBU4BTC1LIT	pH 4.01 Buffer Solution (Red)	
ECBU7BTC1LIT	pH 7.00 Buffer Solution (Yellow)	
ECBU10BTC1LIT	pH 10.01 Buffer Solution (Blue)	

pH Buffer Sachets (20 x 20 ml Per Box)

ECBU4BS	pH 4.01 Buffer Sachets (NIST Traceable ,20 x 20 ml Per Box)	
ECBU7BS	pH 7.00 Buffer Sachets (NIST Traceable ,20 x 20 ml Per Box)	
ECBU10BS	pH 10.01 Buffer Sachets (NIST Traceable ,20 x 20 ml Per Box)	
ECRINWT	pH Deionized Water Rinse Sachets (NIST Traceable ,20 x 20 ml Per Box)	

ORP Solutions (480 ml Per Bottle)

ECORPPRE	Pre-treatment Solution (475 mV)	
----------	---------------------------------	--

ECORPQUIN	Quinhydrone 263 (263 mV, $\pm 15\text{mV}$ to $\pm 30\text{mV}$ @ 25°C)	
ECORPQUIN086	Quinhydrone 86 (86 mV)	
Other Solutions (480 ml Per Bottle)		
ECRE001	Saturated Potassium Chloride with Silver Chloride for Single Junction pH Electrodes	
ECRE002	Saturated Potassium Chloride for Double Junction pH Electrodes	
ECRE005	480 mL Storage Solution for pH electrodes	
ECDPCBT	480 mL Protein Cleaning Solution for pH electrode	
EC636430	Skylite refilling reference electrolyte for EC620130 pH electrode , 60ml	
Conductivity/TDS Calibration Standards		
Conductivity Standard Solutions (480 ml Per Bottle)		
ECCON84BT	84 $\mu\text{S}/\text{cm}$ KCl Calibration Solution	
ECCON100BT	100 $\mu\text{S}/\text{cm}$ KCl Calibration Solution	
ECCON500BT	500 $\mu\text{S}/\text{cm}$ KCl Calibration Solution	
ECCON1413BT	1413 $\mu\text{S}/\text{cm}$ KCl Calibration Solution	
ECCON2764BT	2764 $\mu\text{S}/\text{cm}$ KCl Calibration Solution	
ECCON1288BT	12.88 mS/cm KCl Calibration Solution	
ECCON1118BT	111.8 mS/cm KCl Calibration Solution	
ECCON5000BT	5.0 mS/cm KCl Calibration Solution	
Conductivity/Salinity Sachets (20 x 20 ml Per Box)		
ECCON10BS	10 $\mu\text{S}/\text{cm}$ KCl Conductivity Sachets (NIST Traceable ,20 x 20 ml Per Box)	
ECCON447BS	447 $\mu\text{S}/\text{cm}$ KCl Conductivity Sachets (NIST Traceable ,20 x 20 ml Per Box)	
ECCON1413BS	1413 $\mu\text{S}/\text{cm}$ KCl Conductivity Sachets (NIST Traceable ,20 x 20 ml Per Box)	
ECCON2764BS	2764 $\mu\text{S}/\text{cm}$ KCl Conductivity Sachets (NIST Traceable ,20 x 20 ml Per Box)	
ECCON15000BS	15000 $\mu\text{S}/\text{cm}$ KCl Conductivity Sachets (NIST Traceable ,20 x 20 ml Per Box)	
ECCON3000BS	3000 ppm KCL Salinity Calibration Sachets (NIST Traceable ,20 x 20 ml Per Box)	
TDS 442 Standard Solutions (480 ml Per Bottle)		
EC44250BT	50 ppm 442 Calibration Solution	
EC442300BT	300 ppm 442 Calibration Solution	
EC4421000BT	1000 ppm 442 Calibration Solution	
EC4423000BT	3000 ppm 442 Calibration Solution	
NaCl Calibration Solutions (480 ml Per Bottle)		
ECNACL5PPT	5 ppt Nacl Calibration Solution	
ECNACL25PPT	25 ppt Nacl Calibration Solution	
ECNACL45PPT	45 ppt Nacl Calibration Solution	

Order Code	Description
pH/ORP Controller	
Wall/Panel-mounted ¼ DIN Alpha pH 560 Controller*	
TSPHCP0560	Alpha PH560 pH/ORP Controller with 2 relay outputs
*Note: Operating voltage is 9 VDC and 12 to 24 VDC. Unit is packed with instrument, side thread rods/brackets for mounting and 110 VAC & 220VAC to 9VDC power adapters.	
Wall/Panel-mounted ¼ DIN Alpha pH 550 Monitor*	
TSPHCP0550	Alpha PH550 pH/ORP Monitor (Unit only)
*Note: Operating voltage is 9 VDC and 12 to 24 VDC. Unit is packed with instrument, side thread rods/brackets for mounting and 110 VAC & 220VAC to 9VDC power adapters.	
Wall/Panel-mounted ¼ DIN Alpha pH 500 Series Transmitter*	
TSPHCTP0500	Alpha pH500 pH/ORP 2-Wire Transmitter with 4-20mA Output and 12-24VDC (Unit only)
*Note: Operating voltage is 12 to 24 VDC. Unit is packed with instrument and side thread rods/brackets for mounting.	



pH/ORP Electrodes	
EC100GTSO05B	Ryton-body pH Combination Electrode with Pt 100 RTD (ATC) with 5m connecting cable with BNC and connector for PMP and Pt 100
EC100GTSO10B	Ryton-body pH Combination Electrode with Pt 100 RTD (ATC) with 10m connecting cable with BNC and connector for PMP and Pt 100
EC100GTSO20B	Ryton-body pH Combination Electrode with Pt 100 RTD (ATC) with 20m connecting cable with BNC and connector for PMP and Pt 100
ECARTSOHF05B	Ryton-body pH Combination Electrode without ATC with 5m connecting cable with BNC connector. HF Resistant Glass. Ideal for application having hydrofluoric acid
ECARGTSO05B	Ryton-body pH Combination Electrode without ATC with 5m connecting cable with BNC and connector for PMP
ECARHTTSO05B	Ryton-body pH Combination Electrode without ATC with 5m connecting cable with BNC Connector. High temperature applications up to 110 oC
ECARTSO05B	Ryton-body pH Combination Electrode without ATC with 5m connecting cable with BNC Connector
ECHTAUTSO05B	Ryton-body ORP Gold Electrode without ATC with 5m connecting cable with BNC and connector for PMP
ECHPTTTSO05B	Ryton-body ORP Platinum Electrode without ATC with 5m connecting cable with BNC and connector for PMP
ECFC7252203B	General Purpose Plastic-body double junction pH Combination Electrode, 12x110 mm, 2m cable length (for pH field monitor)
ECFC7252205B	General Purpose Plastic-body double junction pH Combination Electrode, 12x110 mm, 5m cable length (for pH field monitor)
ECFC7960202B	General Purpose Epoxy-body double junction ORP Electrode, 12x110 mm, 2m cable length (for ORP field monitor)



ECFC7960205B	General Purpose Epoxy-body double junction ORP Electrode, 12x110 mm, 5m cable length (for ORP field monitor)
--------------	--

Conductivity/ TDS / Resistivity Controller / Transmitters

Panel-mounted ¼ DIN Alpha COND 2000P Conductivity Series Controller / Transmitter*

TSCONCTP2000P	Alpha COND2000 Conductivity Controller/Transmitter with 4-20 mA Output and 85-250 VAC/DC (Unit Only). Features include Proportional/Proportional Integral Control, Independent Alarm Setpoints with Hysteresis, Scaleable Output, Choice of 2- or 4-cell electrode, etc.
---------------	--

Wall/Panel-mounted ¼ DIN Alpha COND 560 Controller*

TSCONCP0560	Alpha COND560 Conductivity Controller with 2 relay outputs
-------------	--

*Note: Operating voltage is 9 VDC and 12 to 24 VDC. Unit is packed with instrument, side thread rods/brackets for mounting and 110 VAC & 220VAC to 9VDC power adapters.

Wall/Panel-mounted ¼ DIN Alpha COND 550 Monitor*

TSCONCP0550	Alpha COND550 Conductivity Monitor (Unit only)
-------------	--

*Note: Operating voltage is 9 VDC and 12 to 24 VDC. Unit is packed with instrument, side thread rods/brackets for mounting and 110 VAC & 220VAC to 9VDC power adapters.

Wall/Panel-mounted ¼ DIN Alpha COND 500 Series Transmitter*

TSCONCTP0500	Alpha COND500 Conductivity 2-Wire Transmitter with 4-20mA Output and 12-24VDC (Unit only)
--------------	---

*Note: Operating voltage is 12 to 24 VDC. Unit is packed with instrument and side thread rods/brackets for mounting.

Conductivity/TDS/Resistivity Electrodes

ECCS10-0-01T	Conductivity/Resistivity Electrode with Pt100, Cell constant K=0.01, Titanium with 25-foot cable length, tinned open-ended. For Ultra-Pure Water. (With 1/2 Inch Nylon Plastic CapThreading)
ECCS10-0-01TS	Conductivity/Resistivity Electrode with Pt100, Cell constant K=0.01, Titanium with 25-foot cable length, tinned open-ended. For Ultra-Pure Water. (With 1/2 Inch Stainless Steel CapThreading)
ECCS10-0-01S	Conductivity/Resistivity Electrode with Pt100, Cell constant K=0.01, Stainless Steel with 25-foot cable length, tinned open-ended. For Pure, Boiler Feed water, Power Plant and Condensate Water. (With 1/2 Inch Nylon Plastic CapThreading)
ECCS10-0-01SS	Conductivity/Resistivity Electrode with Pt100, Cell constant K=0.01, Stainless Steel with 25-foot cable length, tinned open-ended. For Pure, Boiler Feed water, Power Plant and Condensate Water. (With 1/2 Inch Stainless Steel CapThreading)
ECCS10-0-1S	Conductivity Electrode with Pt100, Cell constant K=0.1, Stainless Steel with 25-foot cable length, tinned open-ended. For Boiler Feed water, Power Plant and Condensate Water. (With 1/2 Inch Nylon Plastic CapThreading)
ECCS10-0-1SS	Conductivity Electrode with Pt100, Cell constant K=0.1, Stainless Steel with Teflon insert and 25-foot cable length, tinned open-ended. For Boiler Feed water, Power Plant and Condensate Water. (With 1/2 Inch Stainless Steel Cap Threading)



ECCS10-0-1SSP	Conductivity Electrode with Pt100, Cell constant K=0.1, Stainless Steel with PEEK insert and 25-foot cable length, tinned open-ended. For Boiler Feed water, Power Plant and Condensate Water. (With 1/2 Inch Stainless Steel CapThreading)	
ECCS10-1-0S	Conductivity Electrode with Pt100, Cell constant K=1.0, Stainless Steel with 25-foot cable length, tinned open-ended. For General Purpose Applications. (With 1/2 Inch Nylon Plastic CapThreading)	
ECCS10-1-0SS	Conductivity Electrode with Pt100, Cell constant K=1.0, Stainless Steel with Teflon insert and 25-foot cable length, tinned open-ended. For General Purpose Applications. (With 1/2 Inch Stainless Steel Cap Threading)	
ECCS10-1-0SSP	Conductivity Electrode with Pt100, Cell constant K=1.0, Stainless Steel with PEEK insert and 25-foot cable length, tinned open-ended. For General Purpose Applications. (With 1/2 Inch Stainless Steel Cap Threading)	
ECCONSEN88X	Conductivity Graphite 2-Ring Epoxy-body Electrode with Pt100, Cell constant K=1.0, tinned open-ended, 12 x 110mm, 7.5m cable length. For General Purpose Applications (CON200/TDS200).	
ECCONSEN89X	Conductivity Graphite 2-Ring Epoxy-body Electrode with Pt100, Cell constant K=0.1, tinned open-ended, 12 x 110mm, 7.5m cable length. For General Purpose Applications (COND200/TDS200).	

Dissolved Oxygen Transmitter

Amperometric Panel-mounted Alpha DO 2000 Series Controller/Transmitter*

TSDOCTP2000PPG	Alpha DO2000 DO Controller/Transmitter (Polarographic) with 4-20 mA Output and 85-250 VAC/DC (Unit Only). Features include Proportional/Proportional Integral Control, Independent Alarm Set points with Hysteresis, Scaleable Output, etc.	
----------------	---	--

*Note: No power cord, electrode and temperature probe is provided. Unit is packed with instrument and side thread rods/brackets for mounting.

Dissolved Oxygen Electrode

EC237150	Polarographic probe with 22 KOhm NTC, 5 m tinned open-ended cable	
----------	---	--

PRICES , MODELS AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE