

thermo scientific



## Thermo Scientific Heracell VIOS 160i CO<sub>2</sub> Incubator with Cell Locker System

**Protected chambers for your  
most sensitive cells**

**ThermoFisher**  
SCIENTIFIC

# A breakthrough in **cell culture management**

The Thermo Scientific™ Heracell™ VIOS 160i CO<sub>2</sub> incubator with the Thermo Scientific™ Cell Locker™ System combines our leading technology with an innovative, patented solution of removable, protected chambers designed for improved culturing efficiency and security for sensitive cultures, such as stem and primary cells, used in cutting edge applications.

Enhancing the advanced features of the Heracell VIOS 160i CO<sub>2</sub> incubator, the Cell Locker System is a breakthrough for cultures in frequently opened or shared use incubators.



## Enhance Your

### Stability

Preserve the environment in Cell Lockers when a neighboring chamber is opened, minimizing sample variability




## Protection

Provides security from cross contamination due to culture isolation in separate chambers



## Flexibility

Organize cultures by separating multiple users, cell types or projects



# ...that maximizes **your sample security**



### **Isolate cultures and projects**


The Cell Locker System features up to six individual, autoclavable polycarbonate chambers that divide the incubator chamber, isolating individual cell types or projects. Individual Cell Lockers serve to quarantine cell types or different projects, offering enhanced protection for valuable cultures.

### **Cross Contamination Protection**

Each Cell Locker has dual 0.2  $\mu\text{m}$  membrane filters that permit air circulation but exclude microbial contaminants. Independent tests demonstrate that microorganisms cannot pass between closed chambers.

### **Minimize environmental variation**

When one Cell Locker is opened, the remaining five Cell Lockers maintain the ideal growth environment for sensitive stem cells, primary cells, diagnostic tests and more.




# Enhanced Stability

Ensure cultures spend more time in conditions that best mimic the *in vivo* state.

While incubation conditions are normally disrupted by routine door openings, the Cell Locker System helps to minimize this impact. During a door opening of one Cell Locker, the temperature, CO<sub>2</sub> gas concentration and humidity remain stable in the unopened Cell Lockers. Compared to traditional incubator designs, the cell cultures in the Cell Locker Solution are in the desired *in vivo*-like state longer because they are not exposed to every door opening.

THRIVE active airflow gently and evenly distributes humidified, conditioned air throughout Cell Lockers, creating a uniform culture environment in each Cell Locker. THRIVE airflow provides fast recovery from door openings for each opened Cell Locker.



Demonstration of temperature, humidity and CO<sub>2</sub> stability in the unopened Cell Lockers when one Cell Locker (#3 as an example) is opened.

## Learn more about the improved culture conditions in the Cell Locker System

- For consistent results, the uniformity in each Cell Locker is  $\pm \leq 0.3^{\circ}\text{C}$
- When one Cell Locker is opened, the other Cell Lockers maintain stable conditions\*, preserving the *in vitro* environment
- Compared to the standard single glass door design, the temperature drop in the opened Cell Locker is reduced by 50%
- With the Cell Locker system, gas consumption from a door opening is reduced by 50%, saving time and money

For more information, see “Functional Performance and Benefits of the Thermo Scientific Cell Locker System”

\*Conditions remain stable within these spatial deviations: temperature  $\pm 0.3^{\circ}\text{C}$ , humidity  $\pm 3\%$ , and CO<sub>2</sub>  $\pm 0.2\%$



# Enhanced Protection

Individual chambers maximize security against costly cross contamination.

Cross contamination from neighboring cultures or circulating microorganisms is a constant risk in many traditional incubators. In the Heracell VIOS CO<sub>2</sub> incubator, the HEPA system filters the entire incubator air volume to achieve ISO Class 5 cleanroom air quality. The Cell Locker further protects from cross contamination by dividing the incubator into six individual chambers. Each individual Cell Locker is effectively a quarantine chamber. Independent 3rd party tests validate protection against circulating microorganisms (when used as directed).



The replaceable 0.2 µm membrane filter has an effective pore size of about 0.02 µm when filtering air<sup>1</sup> and is hydrophobic, oleophobic, resistant to organic solvents and tested for biosafety and low cytotoxicity.

**Table 1:**

Independent tests show common cell culture contaminants were unable to enter or exit a closed Cell Locker. Two common cell culture contaminants were tested in the Cell Locker System inside the Heracell VIOS CO<sub>2</sub> incubator. No microorganisms were able to travel into or out of the Cell Lockers.


For more information, see “How does the Thermo Scientific Cell Locker System isolate cell cultures and projects in a CO<sub>2</sub> incubator, protecting from cross-contamination?”

Independent Tests with Cell Locker System			
Microorganism Tested	Total Circulated	Total Outside Cell Lockers	Total Inside Cell Lockers
<i>Staphylococcus aureus</i> ATCC 6538	9.6 x 10 <sup>4</sup>	TNTC*	0**
<i>Mycoplasma orale</i> DSM 25590	9.3 x 10 <sup>4</sup>	TNTC*	0**

\*TNTC = too numerous to count. For each test, 48 open agar plates were placed outside of the Cell Lockers.


\*\*A total of 24 culture plates were placed open inside the Cell Lockers. All showed zero growth.

<sup>1</sup>Boomus M. Medical Device & Diagnostic Industry News Products and Suppliers. 2006.



# Enhanced Flexibility

The Cell Locker can be configured to fit the unique needs of your lab.




## Cell Locker configuration can be optimized for your workflow

The Cell Locker was designed with flexibility in mind. Different cell types, samples, users or projects can be segregated within shared incubator space.

- Dishes and flasks can be removed individually; on a work tray; or inside the entire Cell Locker with optional transport cover, thus protecting samples from outside air
- Each Cell Locker holds 9 each T-75 cell culture flasks, 20 each 6-well plates, or 24 each 96-well plates
- The Cell Locker can be manually disinfected or can be autoclaved a maximum of 12 times
- Individual Cell Lockers can be placed in any incubator to quarantine samples or to isolate cultures or projects



The non skid tray slides out to allow access to culture vessels, or the entire tray can be removed. The specialized design prevents tipping.



Remove the Cell Locker with optional transport cover to protect all cultures from outside air, for transport to a biological safety cabinet or to another lab.

# Thermo Scientific Heracell VIOS 160i CO<sub>2</sub> Incubator

## with the Cell Locker System

Our advanced technologies deliver the optimized, protected growth environment required to support a range of cell culture needs. Equipped with the Cell Locker System, the Heracell VIOS CO<sub>2</sub> incubator is designed to maximize the level of security for today's demanding research applications.

- 165 L interior chamber with the new 6 segmented, gas tight inner door configuration and 3 shelves designed to accommodate 6 individual Cell Lockers
- Choose electropolished stainless steel or 100% pure copper chamber interior
- THRIVE airflow technology provides enhanced stability, tight uniformity, and fast recovery
- Unique covered humidity reservoir maximizes humidity without condensation
- ISO Class 5 HEPA filtration provides clean room air quality in the chamber
- Thermo Scientific Steri-Run overnight 180°C sterilization cycle achieves 12 log Sterility Assurance Level (SAL) total sterilization
- Thermo Scientific iCAN touchscreen interface provides bright at-a-glance monitoring and complete data visibility to monitor all incubator interactions and parameters
- Temperature resistant, bulb-free IR CO<sub>2</sub> sensor (IR180Si)
- Optional O<sub>2</sub> control of 1-21% or 5-90%

HERAcCell VIOS 160i  
CO<sub>2</sub> Incubator



# Ordering Information

Heracell VIOS 160i Cell Locker Solution Packages with 6 Cell Lockers	Stainless Steel Interior	100% Copper Interior
Single Chamber configured with 6 door gas tight screen, IR180Si CO <sub>2</sub> sensor and 6 each of the Cell Lockers, 120V 50/60HZ	51032124CL6	51032128CL6
Single Chamber configured with 6 door gas tight screen, IR180Si CO <sub>2</sub> sensor, 1-21% O <sub>2</sub> control option, and 6 each of the Cell Lockers, 120V 50/60HZ	51032342CL6	51032406CL6

**Incubator base model includes 6 door gas tight screen and modified interior and shelving (does not include Cell Lockers). Use these part numbers if adding factory installed options.**

Heracell VIOS 160i CO <sub>2</sub> Incubators	Stainless Steel Interior	100% Copper Interior
Single Chamber with IR180Si CO <sub>2</sub> sensor, 120V 50/60HZ	51032124	51032128

## Factory installed options

51901143	Internal 4-20 mA analog data output
51900293	Left hinge door configuration
51900735	Internal gas guard for CO <sub>2</sub>
51900736	Internal gas guard for N <sub>2</sub> /O <sub>2</sub>
51901126	Stainless steel external outer casing
51901137	1-21% O <sub>2</sub> control
51901138	5-90% O <sub>2</sub> control

## Choose customer installable accessories\*

50145394	Support frame for double chamber, 172 mm high (with casters)
50154551	Lower profile support frame for double chamber (with casters), 73 mm high
50148171	Adaptor required for stacking VIOS models
50153148	Replacement membrane filters (2/pk)
50151650	Single Cell Locker with stainless steel sliding tray and transport cover
50154739	Single Cell Locker with copper sliding tray and transport cover
50151650X6	Package of 6 Cell Lockers with stainless steel sliding tray and transport cover
50154739X6	Package of 6 Cell Lockers with copper sliding tray and transport cover

\*Please consult the Heracell VIOS brochure for additional available accessories

Find out more at [thermofisher.com/co2](http://thermofisher.com/co2)

Australia +61 39757 4300  
 Austria +43 1 801 40 0  
 Belgium +32 9 272 54 82  
 China +800 810 5118, +400 650 5118  
 France +33 2 2803 2180  
 Germany national toll free 0800 1 536 376  
 Germany international +49 6184 90 6000  
 India toll free 1800 22 8374  
 India +91 22 6716 2200

Italy +39 02 95059 552  
 Japan +81 3 5826 1616  
 Korea +82 2 2023 0600  
 Netherlands +31 76 579 55 55  
 New Zealand +64 9 980 6700  
 Nordic/Baltic/CIS countries  
 +358 10 329 2200  
 Russia +7 812 703 42 15, +7 495 739  
 76 41

Singapore +82 2 3420 8700  
 Spain/Portugal +34 93 223 09 18  
 Switzerland +41 44 454 12 12  
 UK/Ireland +44 870 609 9203  
 USA/Canada +1 866 984 3766

Other Asian countries +852 3107 7600  
 Countries not listed +49 6184 90 6000

**ThermoFisher**  
 S C I E N T I F I C