Thermo Scientific RP4 Windshielded Rotor



ROTOR SPECIFICATIONS

Туре	Swinging Bucket
Material	Rotor Body Stainless Steel; Bucket Aluminum
Capacity (Bottle) Capacity (Blood Bag)	4 x 1000 mL 8 x 550 mL
Maximum Speed	4,250 rpm; 4,000 rpm ¹
Bucket Dimensions W x L x D (Rectangular)	159 x 170 x 155 mm
Angle	90°
K Factor (Round) K Factor (Rectangular)	12,994; 14,669¹ 11,628; 13,127¹
Warranty	7 years

	RCF	RADIUS
Maximum (Round)	5,513 xg; 4,883 xg ¹	273.0 mm
Minimum (Round)	2,180 xg; 1,931 xg ¹	108.0 mm
Maximum (Rectangular)	5,372 xg; 4,758 xg ¹	266.0 mm
Minimum (Rectangular)	2,342 xg; 2,075 xg ¹	116.0 mm

ROTOR AND ACCESSORIES ORDERING INFORMATION

		THERMO SCIENTIFIC KR4i Series
RP4 Windshielded	Max. Speed	4,250 rpm
	Max. RCF	5,372 xg

RP4 Windshielded Rotor Package includes:

Description	Cat. No.							
RP4 Windshielded Rotor	11178250							
Lubricant	76003500							
Instruction Manual	50114404							

Accessories:

Description	Cat. No.
RP4 Windshielded Rotor Lid	11178073
Round Bucket (qty. 4)	11178143
Rectangular Bucket (qty. 4)	11178108

LABWARE ORDERING INFORMATION (Rectangular Bucket)

Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Oty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (xg)	Dims ØxL (mm)	REQUIRED TUE Type	BE CLOSURES, AD Cat. No.	OAPTERS, ' Oty. /Pkg.	TOOLS & ACCESSORIES Description
450.0- 500.0	-	Quin/Quad Blood Bag with 1 partition	_	-	8	4,250	5,372	-	Adapter	11178158	1	For Blood Bag Liner
450.0- 500.0	-	Quin/Quad Blood Bag without partition	-	-	8	4,250	5,372	-	Adapter	11178159	1	For Blood Bag Liner
400.0- 500.0	-	Quin/Quad Blood Bag with filter in line	-	-	8	4,250	5,372	-	Adapter	11178170	1	For Blood Bag Liner

¹ Without lid.

^{© 2010} Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.



