Corning Incorporated Life Sciences

Registered ISO 9001

Product Description

Catalog Number:	43146
-----------------	-------

Product Description:

431465

-		-	-				
Component Materials:							
Flask		Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and closures.					
Сар	co 0.2	Virgin High Density Polyethylene, meets <i>USP, Class VI</i> requirements for plastic containers and closures. Heavy metal free (meets <i>CONEG</i> req.) color concentrate. 0.2 µm microporous PTFE membrane, meets <i>USP, Class VI</i> requirements for plastic containers and closures.					
Product Dimensions:							
Length of flask w/cap	-	7.97 in.	Height (depth)	-	1.55 in.		
Width	-	4.38 in.	Tolerances	-	+/- 0.05 in.		

Corning® 150 cm² canted neck flask, vent cap, Non-treated

Sterilization:

The product has been irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 *Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization.* Sterility Assurance Level: SAL 10⁻⁶

Pyrogens:

The product has been tested and has met the criteria established in the current version of ANSI/AAMI ST 72: *Bacterial Endotoxins - Test methodologies, routine testing, and alternative to batch testing.* Results: less than 0.1EU/mL.

Bovine Spongiform Encephalopathy and Transmissible Spongiform Encephalopathy:

This product complies with the latest revision of EMEA/410/01 "Note for Guidance on minimizing the risk of transmitting animal spongiform encephalopathy agents via human veterinary medicine products" by virtue of all bovine derived material having been processed per specific conditions of section 6.4 of EMEA/410/01.

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures. Integrity Testing: Visual Attributes: Packaging: Forward pressurization of the product to 10 inches of water column. Visual and microscopic examination of the product. Inspection for seal and barrier integrity, accurate labeling, and correct product configuration.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Revision Date: 09-16-19

Rev No: 6