

Oven

Constant-Temperature Drying Oven

Features:

- * External material: cold-rolled steel with anti-bacteria powder coating.
- * Stainless steel inner chamber, round angle structure, adjustable shelves.
- * PID control with LED display, soft touch operational key, timing function and over-temperature protection.
- * Door with double-layer tempered glass observation window, adjustable air-tight buckle lock, and silicon rubber seal, which provide good seal ability and efficiently prevent heat loss.

**Technical Parameters:**

Model	BOV-T30C	BOV-T70C	BOV-T140C	BOV-T270C
Capacity	43L	70L	137L	270L
Temp. Range	50~200°C			
Temp. Fluctuation	±1°C			
Ambient Temp.	5~40°C			
Timing Range	1~9999min			
Shelves No.	2 pcs		3 pcs	
Consumption	850W	1000W	2000W	3000W
Power Supply	Standard: 220V±10%, 50/60Hz; Optional: 110V±10%, 60Hz			
Internal Size(W*D*H) mm	350*350*350	400*390*450	500*500*550	600*600*750
External Size(W*D*H) mm	635*615*552	680*653*631	830*665*772	930*765*972
Package Size(W*D*H) mm	780*750*700	870*700*800	960*780*950	1060*880*1150
Gross Weight(kg)	60	70	105	145