

UV Air Sterilizer (Wall Mounted)



BKS-B-600



BKS-B-800



BKS-B-1000

Application:

It is suitable for dynamic indoor air disinfection in class II, III and IV environments of hospitals, such as operating room, delivery room, general protective isolation room, supply room sterile area, burn ward, ICU intensive care unit, pediatric ward, injection room, emergency room, laboratory and etc. Also applicable for homes, schools, libraries, blood stations, food and beverage factories, pharmaceutical factories, sanitary products factories, electronics factories, farms, warehouses, banks, nursing homes, museums, archives, restaurants and other public places.

Features:

- * LED display, there are 20s to display the total running time after shutdown.
- * Two working modes: manual mode and timing mode. Timing can achieve 24h freely set three sterilization periods, and has a memory function.
- * Two kinds of wind direction control: manual and automatic. The wind angle can be adjusted manually.
- * The super-infrared receiving device can realize long-distance remote control.
- * Built-in high brightness, long life, ozone-free, U-type UV lamp.
- * Human and machine coexistence(When there is no ozone).

Technical Parameters:

Model	BKS-B-600	BKS-B-800	BKS-B-1000
Applicable Room	≤60m ³	≤80m ³	≤100m ³
Circulating Air	≥600m ³ /h	≥800m ³ /h	≥1000m ³ /h
Shell Material	ABS, anti-UV		
Filter	Activated carbon filter		
UV Lamp Life	≥5000h		
UV Radiation Intensity(Inner)	≥20000μW/cm ²		
Natural Bacteria Extinction Rate	≥90%		
Sterilization Rate of Staphylococcus Albicans	≥99.9%		
Noise	≤55dB		
Consumption	≤130W	≤160W	≤280W
Power Supply	AC110/220V±10%, 50/60Hz		
Optional Function	Negative ion generator(Amount: ≥3×10 ⁷ ions/cm ³) Ozone generator(Amount: ≥10g/h)		
External Size(W*D*H)	850*190*280mm	980*220*310mm	1097*218*325mm
Package Size(W*D*H)	1002*297*397mm	1002*297*397mm	1196*295*399mm
Net Weight	6.5kg	8.8kg	11kg
Gross Weight	8.75kg	13.05kg	16kg