Corning Incon Life Scier Registere ISO 9001:2	es Product	Description
Catalog Number:	3474	
Product Description:	Costar ® 96-well Ultra Low Attachment Evaporation lid	t Multiple Well Pate, flat bottom, with Low
Component Materials: Plate/Lid-Surface-	Virgin Polystyrene, meets <i>USP, Class V</i> closures Proprietary hydrogel.	// requirements for plastic containers and
Product Dimensions: Length of Plate Width of Plate		of Well @ top270 in. of Well @250 in.
Depth of Well Tolerances of Dimensions	420 in. Height wit - +/ 010 in. Growth Ar	

Sterilization:

The product is irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 *Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization.* Sterility Assurance Level: SAL 10⁻³

Pyrogens:

The product has been tested and has met the criteria established in the current version of ANSI/AAMI ST 72:2002/(R)2010 Bacterial Endotoxins - Test methodologies, routine monitoring, and alternative to batch testing. Results: $\leq 0.1 \text{ EU/mL} (\leq 4 \text{EU/device})$

Surface Characterization:

Surface is characterized to be hydrophilic and neutrally charged, composed of a covalently bound hydrogel layer that is biologically inert and non-degradable. This surface composition has been optimized for cell attachment inhibition.

Cell Attachment and Growth Characteristics:

The product has been tested for the attribute of cell attachment inhibition utilizing an attachment- dependent mammalian cell line in a serum supplemented media. Cell attachment inhibition must be \geq 98% as compared to a standard tissue culture treated surface.

Bovine Spongiform Encephalopathy and Transmissible Spongiform Encephalopathy:

This product does not contain materials of animal origin.

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures. Visual Attributes: Visual and microscopic examination of the product. Packaging: Inspection for seal and barrier integrity, accurate labeling, and correct product configuration.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 16