thermoscientific

Ultracentrifuge Rotors

Thermo Scientific TN-1865 Rotor



ROTOR SPECIFICATIONS

Туре	Neo Angle
Material	Titanium
Capacity	18 x 5 mL
Maximum Speed	65,000 rpm
Tube Dimensions Ø x L	13 x 53 mm
Angle	10°
K Factor	15
Max. Sample Density	1.7 g/mL
Net Weight	8.7 kg/19.1 lbs
Warranty	5 years

	RCF	RADIUS
Maximum	430,874 xg	91.3 mm
Average	383,681 xg	81.3 mm
Minimum	336,317 xg	71.2 mm

ROTOR AND ACCESSORIES ORDERING INFORMATION

		THERMO SCIENTIFIC			
		Sorvall WX and WX+ Series			
TN-1865	Max. Speed	65,000 rpm			
	Max. RCF	430,874 xg			

TN-1865 Rotor Package includes:

Description	Cat. No.
TN-1865 Rotor	75003035
Caps (18)	
Cap O-rings (54)	
Cap Handle	
Optical Speed Disc (2)	
Rotor Stand	
Lubricant	
Vacuum Grease	
Log Book	
Instruction Manual	

Accessories:

Description	Cat. No.	
PA Seal Tube Kit for 5 mL Tubes, includes 100 5 mL PA Tubes / 18 Spacers / Tools	50146082	
Tube Rack for 5 mL PA Tube	50146076	
STF3 (Tube Sealer) 110V (CSA)	50146078	
STF3 (Tube Sealer) 200-240V (CE Mark)	50146079	

LABWARE ORDERING INFORMATION

									REQUIRED TUBE CLOSURES, ADAPTERS, TOOLS & ACCESSORIES			
Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Qty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (xg)	Dims ØxL (mm)	Туре	Cat. No.	Qty. /Pkg.	Description
5.0	5.1	PA Seal Tube	50146014	50	18	90,000	645,101	13 x 53	PA Seal Tube Kit ¹	50146082	1	PA Seal Tube Kit for 5 mL tubes

¹ 50146078 or 50146079 required.

Find out more at thermofisher.com/rotors

© 2017 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

