Corning Incorporated Life Sciences

Registered ISO 9001

Catalog Number BP50-01

PDS reference PDS_Cbor_1970 Version _ 1

Product description Corning® Gosselin™ Petri Dish 60 x 15 mm, No Vent, Double Outer Bag, 15/Bag, 1620/Case

Sanitary Assurance LevelASEPTIC products are manufactured in a controlled environment, without human intervention during the manufacturing process.
Finished products with an Aseptic claim are not subjected to sterilization and do not make a claim to have a Sterility Assurance Level.

Expiration Statement

Performance testing (AQL)Inspection based on a statistically significant number of samples towards to internal or agreed specifications that determine Assurance Quality Level.

$\begin{array}{c} \textbf{Primary body composition} \\ \textbf{PS} \end{array}$

Closure

No Vent

Special feature

N/a

Packaging

Double Outer Bag, 15/Bag, 1620/Case

Regulation Statement

We hereby confirm that we and/or our raw materials suppliers do not intentionally use the following substances in the manufacturing of

- LATEX
- BISPAENOL A (CAS No 80-05-7) PHTHALATES as per Regulation 1907/2006/EC (SVHC).

Raw material suppliers also guarantee the following requirements through certificates of compliance:

- EU Food Contact 1935/2004/EC and 10/2011/EU. However, our finished products have not been validated for food contact applications. They are designed for laboratory applications only.
- BSE/TSE compliant: the animal origin materials and/ or derived materials were not intentionally used during manufacturing process. As such, our finished products do not contain substances considered at risk for transmitting BSE/TSE.
- Complies to REACH SVHC candidate list (Regulation 1907/2006/EC). Do not contain more than 0.1% (w/w) of any substance of very high concern listed in the ECHA candidate list in accordance with Article 33 of the Reach Regulation.
- Heavy Metals as per directive 94/62/EC: meets the relevant requirements on packaging and packaging waste. The sum of the concentration Cd, Cr (VI), Hg and Pb does not exceed 100 ppm.

Hugues Vanderschelden Plant Quality Manager, Borre vandersch2@corning.com