Corning Incorporated Life Sciences

Registered ISO 9001:2008

Product Description

Catalog Number: 3374

Product Description: Corning ® HTS Transwell ® 96 Well, TC Treated, 8.0 µm pore size, with barcode

label, in a receiver plate with lid

Component Materials:

Receiver Plate - Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and

closures.

Lid - Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and

closures.

Transwell body - Virgin Polystyrene, meets USP, Class VI requirements for plastic containers and

closures.

Filter - Transparent polyester membrane, meets USP, Class VI requirements for plastic

containers and closures.

Adhesive - Proprietary Acrylate, meets ISO 10993 Biocompatibility requirements.

Barcode Label: - White polypropylene base, acrylic adhesive

Special Format:

Barcode label (format 128) on A1 short side

Product Dimensions:

Length of Plate - 5.030 in. Bottom of Transwell to - .050 in.

receiver plate

Width of Plate - 3.365 in. Apical volume added/ - $75\mu L$

Transwell per well

Height in receiver with lid - .770 in. Bisolateral volume added - 235µL

per receiver plate well

Tolerances of - +/-.010 in. Suggested working - 75μL (A) to 235μL (B)

Dimensions

Maximum volume - 100μL (A) to 290μL (B)

Sterilization:

The lot has been irradiated and dosimetrically released based on ANSI/AAMI/ISO 11137 Sterilization of healthcare products-Requirements for validation and routine control-Radiation sterilization.

Sterility Assurance Level: SAL 10⁻³

Performance Testing:

Each manufacturing lot is sampled and tested in accordance with Standard Operating Procedures.

Visual Attributes: Visual examination of the product.

Packaging: Inspection for seal and barrier integrity, accurate labeling, and correct

product configuration.

Cell Culture Treatment of Membrane: Wettability test using water to insure the presence of a hydrophilic

surface.

Lot Number Designation:

8 Digit Lot Number: First 3 digits - Julian date, start of manufacturing; Next 2 digits - Year of manufacture; Last 3 digits - Batch identification.

Rev No: 2