BIOBASE®

Washer Disinfector (Lab Automatic Glassware Washer)





BK-LW120 BK-LW220/320

Introduction:

The lab glassware washers integrate programmed cleaning, disinfecting and drying functions to clean all glassware stuff, for beaker, flask, pipette, petri dish, burette, measuring cylinder, test tube etc.


Features:

- * High efficient cleaning system, designed with European reliable pump, optimized spray arm and nozzles, and self-cleaning program;
- * Rapid and efficient drying system, designed with independent air heater, HEPA filter and drying process;
- * Water heating temperature can reach 99°C, while hot air drying temperature can reach 120°C;
- * Professional configuration design—stainless steel for corrosion resistance; reinforced glass window mounted to achieve a clear view on washing process;
- * PLC touch screen control with preset 12 programs and 99 cutomized programs
- * Safety protection—electronic security door lock to prevent unexpected door opening, water & drying air temperature dual control and equipped with emergency switch.

Standard Washing Procedure (can be self-designed by the user):

Pre-cleaning→Washing with cleaner→Rinse→Washing with neutralization→Rinse→Washing with hot water→Drying

All cleaning racks can be removed completely, convenient to washing rack pipeline:



Standard Rack (BKIR36)



Beaker Rack (BKBR01)



Combined Rack (BKIR11218)



Measuring
Cylinder Rack
(BKIR38)



Injection Rack (BKIR30)



Petri-dish Rack-Lower (BKPDR9075L)



Petri-dish Rack-Upper (BKPDR9075U)



Pipette Rack (BKPR60)



Rubber Tube Rack (BKRTR20)

Technical Parameters:

Model	BK-LW120	BK-LW220	BK-LW320	
Capacity	120L	220L	320L	
Water Consumption/Cycle	15L	yblobaso.ut	AH'	
Inlet Water Pressure	0.03~0.8Mpa			
Noise	≤50dB	≤55dB	≤55dB	
Material	Internal materia: SS316, Outer material: SS304			
Overall Power Consumption	6KW	6.5/16.5KW	6.5/18KW	
Power Consumption-Water Washing	0.75KW		1.5 KW	
Power Consumption-Water Heating	5KW	5/15KW	5/15KW	
Power Consumption-Drying	2.1KW	3.6KW	3.6KW	
Power Supply	AC220V, 50Hz	AC220V, 50Hz; 380	AC220V, 50Hz; 380V, 50Hz	
Cleaning Racks	1 pcs	2 pcs	3 pcs	
Standard Cleaning Racks	BKIR36*1	BKIR36*2	BKIR36*3	
Standard Accessories	One bucket RBS A 155 leaner (1 L), One bucket RBS A 375 neutralizer (1 L)			
Optional Accessories	USB interface, printer, Cleaning racks			
Washer Chamber Size(W*D*H)mm	600*629*465	600*629*658	600*629*820	
External Size(W*D*H)mm	960*740*850	780*690*1760	790*690*1950	
Package Size(W*D*H)mm	1100*950*1050	1000*850*2100	1000*840*2180	
Gross Weight(kg)	145	330	350	

53