

B-Class Steam Vacuum Autoclaves

Features:

1. Fully compliance to EN13060 B Standard, 3 times pulsating vacuum. Vacuum can down to -80KPa.
2. Large LCD Screen display, easy to operate.
3. Automatically detect door status, make operation more safety.
4. 2.5mm Deep-stretched shape high quality stainless steel internal bladder.
5. Built-in cleaning and sewage equipment. Automatic alarm when water shortage or full.
6. Built-in printer to print the sterilization data.
7. Short-circuit protection, Fuse tube: T15AL~250V
8. Storage tank capacity: 2 Liters.
9. Required water for each loop: 0.3 Liters.
10. Minimum alarm level of water tank: 0.5 Liters.
11. Sterilization (Pressure/Temperature):
 - 90~130KPa/121°C (Standard atmospheric pressure)
 - 200~230KPa/134°C (Standard atmospheric pressure)



Technical Specifications:

Model	INOAClave-B12	INOAClave-B16	INOAClave-B18	INOAClave-B23
Capacity (L)	12	16	18	23
Chamber Size (mm)	200x360	230x350	250x350	250x450
Outside Size (mm)	560x450x410	560x450x410	560x450x410	680x450x410
Package Size (mm)	650x520x520	650x520x520	650x520x520	780x520x520
Weight		50/55kg		